

2220012164

GLC-TE

Cisco GLC-TE 1000BASE-T 1G SFP Transceiver - RJ45



Description

The 1000BASE-T SFP operates on standard Category 5 unshielded twisted pair copper cabling of up to 100m (328 ft) link length. Cisco 1000BASE-T SFP modules support 10/100/1000 autonegotiation and Auto MDI/MDIX.

Specifications

CABLING

Type	Category 5 unshielded twisted pair copper cabling
------	---

DIMENSIONS & WEIGHT

Dimensions (W x D x H)	13.4 x 56.5 x 8.5 mm
Weight	0.075 kg

Used With



IE-3000-4TC

Cisco IE-3000-4TC Switch



IE-3000-8TC-E

Cisco IE-3000-8TC-E Switch w/Layer 3



IE-3000-8TC

Cisco IE-3000-8TC Switch



IE-3000-4TC-E

Cisco IE-3000-4TC-E Switch w/Layer 3

DISCONTINUED



2960+24PC-L/IEC60945

Cisco Catalyst 2960+24PC-L Ethernet Switch Kit - IEC60945 Compliant



3560X-24P-L

CISCO Catalyst 3560X 24-port 10/100/1000 PoE+ LAN Base



3560X-24P-S

CISCO Catalyst 3560X 24-port 10/100/1000 PoE+ IP Base