

2810011067

## CAB-AVIP55-230

Active ventilation unit IP55 for CABxx, 133mm height, 230VAC



- ✓ Roof-mounted fan 220V-240V, 133 mm height
- ✓ Enclosure internal thermostat
- ✓ Thermostat Mounting plate
- ✓ Outlet filter Standard (255x255mm)

---

## Description

CAB-AVIP55-230 is an active ventilation unit intended to be used with the CABxx cabinet range. With IP55 protection, it is intended to be used even in environmentally demanding areas. It can also be used on glazed door cabinets where an air inlet can be mounted on the side or on the back of the cabinet.

\*Includes filter mat for IP55 protection and internal thermostat with mounting plate, 417 m<sup>3</sup>/h

# Specifications

## ELECTRICAL DATA

Rated operating voltage	220 V - 240 V, 1~, 50 Hz/60 Hz
Power consumption	At 50 Hz: 51 W At 60 Hz: 62 W
Air throughput, unimpeded air flow	At 50 Hz: 417 m³/h At 60 Hz: 446 m³/h
IP protection	IP 55 including filter mat

## DIMENSIONS & WEIGHT

Roof mounted fan dimensions (W x H x D)	400x133x400mm
Roof mounted fan mounting cut-out	258x258mm
Roof mounted fan installation depth	34.6 mm
Inlet filter dimensions (W x H x D)	255x255x25mm
Inlet filter mounting cut-out	224x224mm
Weight	5.76kg

## Used With



CAB15F-V2

Floor cabinet 19" 15HU  
600x600x800mm fixed frame



CAB24FW-V2

Floor cabinet 19" 24HU  
800x600x1200mm fixed frame



CAB24FWD-V2

Floor cabinet 19" 24HU  
800x800x1200mm fixed frame



CAB42F-V2

Floor cabinet 19" 42HU  
600x600x2000mm fixed frame



**CAB42FW-V2**

Floor cabinet 19" 42HU  
800x600x2000mm fixed frame



**CAB42FWD-V2**

Floor cabinet 19" 42HU  
800x800x2000mm fixed frame



**CAB24F-V2**

Floor cabinet 19" 24HU  
600x600x1200mm fixed frame



**CAB24SW-V2**

Floor-mounted 24HU cabinet -  
800x1200x600mm (WxHxD)  
swing frame



**CAB42SWD-V2**

Floor cabinet 19" 42HU  
800x800x2000mm swing frame



**CAB42FD-V2**

Floor cabinet 19" 42HU  
600x800x2000mm fixed frame



**CAB42FWDD**

Floor cabinet 19" 42HU  
800x1000x2000mm fixed frame