



2220012402

C1000-48P-4G-L/IEC60945

Cisco C1000 48port 1G PoE+ w/ 4x1G SFP / IEC60945



Description

Cisco Catalyst 1000 Series Switches are fixed managed Gigabit Ethernet and Fast Ethernet enterprise-class Layer 2 switches designed for small businesses and branch offices. These are simple, flexible and secure switches ideal for out-of-the-wiring-closet and critical Internet of Things (IoT) deployments. Cisco Catalyst 1000 operate on Cisco IOS Software and support simple device management and network management via a Command-Line Interface (CLI) as well as an on-box web UI. These switches deliver enhanced network security, network reliability, and operational efficiency for small organizations.

IEC60945 Compliant, DNV Type approved for EXIGO and ACM systems

certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is

Specifications

Cisco Catalyst 1000-48P-4G-L is managed 48-port switch with 48 auto-sensing 10/100/1000 PoE+ ports and 4x Gigabit Ethernet SFP ports .

Includes AC filter, 1-phase, 3A, 250VAC, Din-Rail Mount

PORTS

10/100/1000 RJ45 PoE+	48
SFP	4
Console ports	1x RJ45, USB mini-B and USB-A (for storage and Bluetooth console)

ENVIRONMENT

Operating temperature	-5°to 50°C
Operating relative humidity	5% to 90% at 40°C (non-condensing)

ELECTRICAL CHARACTERISTICS

Frequency	50 to 60 Hz
AC voltage	110 to 220 VAC
Current	4.25A to 2.07A
Maximum power Consumption	434 W
Available PoE Power	370W
Maximum Power Wattage for BTU/hr	500.4

DIMENSIONS & WEIGHT

Dimensions (W x D x H)	445 x 350 x 44 mm
Weight	5.43 kg
Mounting	Rack Mountable, 1HU

page 2/2