

2810010123

## CAB42FWDD

Floor-mounted 42HU cabinet - 800x2000x1000 (WxHxD) fixed frame



- ✓ Front door: Glazed door
- ✓ Front door handle: CAB-DH-K
- ✓ Rear door: Single steel doors
- ✓ Rear door handle: CAB-DH-K
- ✓ Including 4x eyebolts for crane transportation
- ✓ The door hinged on the right, may be swapped to the left
- ✓ Base/plinth not included, can be ordered separately

---

## Description

Our all-new series of multi-use cabinets are designed to be used in a marine environment. This floor-mounted 42HU cabinet is DNV-GL type approved and's perfect for installing our 19" system components to create a complete system for your installation.

The cabinet comes with a front metal door that is hinged on the right, and it can be swapped to the left if needed. The rear side of the cabinet is covered with a fixed metal plate and can be replaced with rear doors if required. Cabinet variant 42 HU, 800 wide and 800 deep. Internal 19-inch fixed frame for up to 42 HU. Includes the choice of DIN rail mounting in the bottom, prepared for optional power switch-over modules and terminals. It has 3 fixed door plates, front doors, and chassis ground.


Multi-part roof plate with cable entry on both sides via brush strips over the whole enclosure depth. The roof incorporates a concealed cut-out to accommodate a CAB-AVT-W-115-230 fan unit for active ventilation. The cover plate can be raised on spacer pillars to support passive ventilation if required.

This cabinet is suitable for:


- ✓ ACM Advanced modules
- ✓ SPA-V2 Public Address
- ✓ EXIGO Public Address
- ✓ Radio
- ✓ LAN
- ✓ CCTV
- ✓ IPTV
- ✓ DECT

- ✓ Paging
- ✓ Masterclock
- ✓ UPS

# Technical Dimensions



CABINET TECHNICAL DATA	
MODEL:	VX 5309.136
COLOR:	RAL 7035
BASE WEIGHT:	185 kg [406 lbs]
BASE/PLINTH:	NO
VENTILATION:	NONE (DEFAULT)
FRONT DOORS:	GLAZED
REAR DOORS:	SINGLE STEEL DOOR
DOOR HANDLE:	DOOR HANDLE W/ KEY-LOCK (DEFAULT)



# Specifications

## GENERAL

Dimensions (WxHxD)	807x2056x1112 mm
Color	RAL 7035
Material	Steel / Glazed front door
Cable inlet	Bottom & top
Ingress grade	IP-55 (or less, based on selected ventilation)
Mounting	Floor mounted
Environmental Condition	Protected

## Accessories



CAB-DH-P

Door handle with push-button for CABxx



CAB-DH-PP

Door handle with push-button & pad-lock for CABxx



CAB-LED

CABxx LED System light w/sensor 100-240VAC, w/connection cable



CAB-CE-S

Cable entry gland w/sealing membranes Ø7 to 26mm



CAB-CE-M

Cable entry gland 14xM25/32



CAB-CE-L

Cable entry gland 2xM25/32/40, 1xM32/40/50, 2xM40/50/160



CAB-1SD-42W

Cabinet steel door 800x2000mm



CAB-2SD-42W

Cabinet double steel door 800x2000mm



### CAB-BASE-810

Base / plinth for 800x1000mm  
cabinets



### CAB-AVT-W-115-230

Active ventilation for CABxx with  
glass door, 115-230VAC