2220012675

C9115AXI-B

Cisco C9115AX Access Point with CAPWAP software - USA(B)

The 9115AX Series Wi-Fi 6 access point is a wireless controller-based product and supports Cisco Catalyst 9800 Series Wireless Controllers, Cisco 3504, 5520, and 8540 Wireless Controllers



CISCO Certified

Description

- 802.11ax (Wi-Fi 6)
- Data rate of up to 5.38 Gbps (160 MHz with 5GHz)
- 4x4 downlink MU-MIMO with four spatial streams
- Integrated antennas:
  - 2.4 GHz, gain 3 dBi
  - 5 GHz, gain 4 dBi
- 1x 100, 1000, 2500 Multigigabit Ethernet (RJ-45) – IEEE 802.3bz
- PoE 802.3at
- Designed with flexible mounting options in mind: Ceiling or wall.

www.zenitel.com info@zenitel.com Last revision date: 2023-09-13 15:10

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

Specifications

ORDER INFORMATION	ACCESS POINT VERSION	DEFAULT LOADED SOFTWARE
2220012674	Cisco C9115AX Access Point with CAPWAP software - EMEA(E)	CAPWAP software
2220012675	Cisco C9115AX Access Point with CAPWAP software - USA (B)	CAPWAP software
2220012676	Cisco C9115AX Access Point with CAPWAP software - Canada (A)	CAPWAP software
2220012680	Cisco AP License for WLC	including 3y DNA On-Prem Essential

DESCRIPTION	
802.11ax	4x4 downlink MU-MIMO with four spatial streams; Uplink/downlink OFDMA; PHY data rates up to 5.38 Gbps (160 MHz with 5 GHz and 20 MHz with 2.4 GHz); TWT; BSS coloring; MRC; 802.11ax beamforming; 20-, 40-, 80-, and 160-MHz channels; Packet aggregation: A-MPDU (transmit and receive), A-MSDU (transmit and receive); 802.11 DFS; CSD support
Integrated antennas	2.4 GHz, gain 3 dBi; 5 GHz, gain 4 dBi
Interfaces	1x 100, 1000, 2500 Multigigabit Ethernet (RJ-45); Management console port (RJ-45); USB 2.0
Indicators	Status LED indicates boot loader status, association status, operating status, boot loader warnings, and boot loader errors
Dimensions (W x L x H)	203 x 203 x 38 mm (Access point without mounting bracket)
Weight	0.9 kg (Access point without mounting bracket)
Operating Temperature	0° to 50°C
Humidity	10% to 90% (non condensing)
Powering options	PoE 802.3at PoE+ or UPOE Ethernet switch or Optional Cisco power injectors
Mounting	Mounting bracket AIR-AP-BRACKET-1= (Included with the access point)

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

OTHER MODELS	
2220012671	Cisco C9105AX Access Point with CAPWAP software - EMEA (E)
2220012672	Cisco C9105AX Access Point with CAPWAP software - USA (B)
2220012673	Cisco C9105AX Access Point with CAPWAP software - Canada (A)

Used With



C9800-L-F-K9

Cisco Catalyst 9800-L Wireless Controller - Fiber Uplink

Item Number: 2220012677



C9800-L-C-K9

Cisco Catalyst 9800-L Wireless Controller - Copper Uplink

Item Number: 2220012678

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.