zenitel

DATASHEET




1200511750

# PSU75

Din Mount Power Supply Unit 230VAC to 24VDC

- Switched Mode Power Supply
- Easily DIN Rail mountable
- Input Voltage 88 - 264V AC
- 3.2A Output, 75W
- 24V DC Output
- Short circuit / Overload / Over voltage / Over temperature protections
- High efficiency 90% and low-power dissipation

Public Address  Voice Alarm  Commercial Audio

## Description

Zenitel's PSU75 is a cost-effective and compact DC power supply (PSU) manufactured by Mean Well. Designed for installation on TS-35/7.5 or TS-35/15 mounting rails, offering a space-saving solution for PAVA cabinets. The PSU complies with EN61000-3-2 standards and features a robust metal housing, ensuring efficient power dissipation. The PSU75 is an excellent choice for PAVA applications requiring additional DC power for peripherals.



www.zenitel.com info@zenitel.com Last revision date: 2025-01-08 13:48

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

# Specifications

Type Switched Mode
Number of Outputs: 1
Input Voltage: AC 88 → 264V
Output Voltage: DC
Output Voltage Adjustment Range24 → 28V
Output Current: 3.2A
Output Power Rating: 75W
Dimensions:125.2 x 32 x 102mm
Standards MetRoHS Compliant, TUV EN 60950-1, UL 508
Special Features: Overvoltage and Short Circuit Protection
Load Regulation±1%
Minimum Operational Temperature: -30°C
Maximum Operational Temperature: +70°C
Mounting Type: DIN Rail Mount



www.zenitel.com info@zenitel.com Last revision date: 2025-01-08 13:48

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.