

2200003006

MP-114-V2

SIP gateway 4 port FXO



Description

- ✔ Connects Vingtor-Stentofon AlphaCom XE system to external telephone systems such as PABXs and the public telephone network
- ✔ Possible to share a gateway between multiple AlphaCom XE nodes (require VoIP AlphaNet license)
- ✔ High audio quality supporting echo cancelling and default simplex switching
- ✔ Web management for easy configuration and installation
- ✔ Cost effective trunking
- ✔ 4 port FXO

Specifications

GENERAL

Usage	Analogue telephone gateway
Telephone interface	FXO Loop-start
Temperature range	Storage: -25° to 85°C / Operational: 5° to 40°C
Humidity range	10% to 90% non-condensing
Dimensions (WxHxD)	220 x 42 x 172mm / 8.67 x 1.66 x 6.78 inches
Power	100 – 240 VAC / 50-60 Hz
Mounting	Rack mount with optional rack-mount kit Table top Wall mount
Ethernet Interface	10/100 Mbps, Base-Tx, RJ45
Network QoS	DiffServ, TOS
Media protocols	RTP (RFC 3550), SRTP (RFC 3711), RTCP (RFC 3550), RTCP-XR (RFC 3611)
Calling Line Identity	Bellcore GR-30-CORE Type 1 using Bell 202 FSK modulation, ETSI Type 1, NTT, Denmark, India, Brazil, United Kingdom and DTMF ETSI CID (ETS 300- 659-1)
EMC compliance	EN55022 Class B, CFR Part 15 Class B, EN55024, EN61000-3- 3, EN61000-3-2, VCCI Class X1 (equal to class B)
	EN60950 1 Safety of IT

Safety compliance	EN60950-1 Safety of IT equipment, UL60950-1 Including compliance to section 6 (over-voltage protection)
Telecom compliance	TRR-21, TIA-968
In-band signalling	DTMF (TIA 464B) User defined and call progress tones