zenitel

DATASHEET

2200003006

MP-114-V2

SIP gateway 4 port FXO



Description

- Connects Vingtor-Stentofon AlphaCom XE system to external telephone systems such as PABXs and the public telephone network
- Possible to share a gateway between multiple AlphaCom XE nodes (require VoIP AlphaNet license)
- High audio quality supporting echo cancelling and default simplex switching
- Web management for easy configuration and installation
- Cost effective trunking
- 4 port FXO

www.zenitel.com info@zenitel.com Last revision date: 2026-03-05 13:33

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

Specifications

GENERAL	
Usage	Analogue telephone gateway
Telephone interface	FXO Loop-start
Temperature range	Storage: -25° to 85°C / Operational: 5° to 40°C
Humidity range	10% to 90% non-condensing
Dimensions (WxHxD)	220 x 42 x 172mm / 8.67 x 1.66 x 6.78 inches
Power	100 – 240 VAC / 50-60 Hz
Mounting	Rack mount with optional rack-mount kit Table top Wall mount
Ethernet Interface	10/100 Mbps, Base-Tx, RJ45
Network QoS	DiffServ, TOS
Media protocols	RTP (RFC 3550), SRTP (RFC 3711), RTCP (RFC 3550), RTCP-XR (RFC 3611)
Calling Line Identity	Bellcore GR-30-CORE Type 1 using Bell 202 FSK modulation, ETSI Type 1, NTT, Denmark, India, Brazil, United Kingdom and DTMF ETSI CID (ETS 300-659-1)
EMC compliance	EN55022 Class B, CFR Part 15 Class B, EN55024, EN61000-3-3, EN61000-3-2, VCCI Class X1 (equal to class

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

	Class X1 (equal to class B)
Safety compliance	EN60950-1 Safety of IT equipment, UL60950-1 Including compliance to section 6 (over-voltage protection)
Telecom compliance	TRR-21, TIA-968
In-band signalling	DTMF (TIA 464B) User defined and call progress tones

www.zenitel.com info@zenitel.com Last revision date: 2026-03-05 13:33

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.