

tbd

SPCB-80W-80-EN54

2-WAY BASS REFLEX FLUSH MOUNT CEILING SPEAKER



- ✓ EN 54-24 CERTIFIED
- ✓ HIGH QUALITY AUDIO FOR VOICE AND BACKGROUND MUSIC
- ✓ 80W / 100V
- ✓ LOW IMPEDANCE OPTION
- ✓ 2-WAY BASS REFLEX CEILING SPEAKER WITH NEODYMIUM TWEETER
- ✓ 8" (200mm) CHASSIS
- ✓ STURDY METAL FIREDOME
- ✓ EASY INSTALLATION WITH QUICK MOUNT CLAMPS



Public Address



Voice Alarm

Commercial Audio



EN 54 Certified

Description

The SPCB-80W-80-EN54 is a 80W 100V ceiling loudspeaker fitted with a Firedome for voice alarm applications. It has an 8" (200mm) 2-way bass reflex loudspeaker chassis with a high-quality neodymium tweeter providing excellent sound quality for speech and background music. Certified to EN 54-24, the speaker is fitted with a 100V transformer with four power level adjustment tapings of 80W, 30W, 15W and 7.5W, selectable using a rotary switch on the front of the speaker, behind the grille. Low impedance operation is also possible.

The sturdy metal Firedome housing in RAL 9016 (traffic white) guarantees long-term durability. For additional reliability, a thermal fuse is provided. The speaker is protected to class IP 21C and the speaker chassis is treated against damp. Easy installation is made possible through quick-mount clamps tightened using a simple screw system. The finely perforated speaker grille can be removed quickly for access to the power rating switch and the grille can be easily replaced by a different coloured grille, even after installation.

Used With



from site

D150

PAVA 150W Power Amplifier
Module for the V2000 / INTEGRA

from site

D500

PAVA 500W Power Amplifier
Module for the V2000 / INTEGRA

V2000

PAVA 2000W Power Amplifier
Mainframe (0 amps Pre Installed)