



tbd

## SPCF-06W-65

### FLUSH MOUNT CEILING SPEAKER

- ✓ HIGH QUALITY AUDIO FOR VOICE AND BACKGROUND MUSIC
- ✓ FLUSH MOUNT CEILING SPEAKER
- ✓ 6W / 100V
- ✓ SIZE 6.5" (165MM) FULL RANGE CHASSIS
- ✓ QUICK AND EASY MOUNTING
- ✓ POWDER COATED METAL CHASSIS

 Public Address  Voice Alarm Commercial Audio

## Description

The SPCF-06W-65 is a 6W 100V flush mount ceiling loudspeaker, which has a 6.5" (165mm) full-range chassis providing excellent sound quality with speech and background music. The speaker is fitted with a 100V transformer which has three power adjustment tapings of 6W, 3W, and 1.5W.

The SPCF-06W-65 has a powder coated metal chassis and grille, with the high quality finish giving good long-term protection and resistance to corrosion. As standard the speaker is coloured to match RAL9010 'Pure White', however the speakers can be supplied in any four-digit RAL or NCS colour, as a special order. Quick and easy ceiling mounting is provided through the use of spring clamps, with a possible ceiling thickness of between 2mm and 45mm. The 100V loudspeaker line cabling is connected by means of a simple and quick two-pin push-clamp.

This loudspeaker is optionally available with a DC blocking capacitor fitted, in order to provide compatibility with DC loudspeaker line monitoring systems. The part number for this DC monitoring compatible version is SPCF-06W-65-DC

## Used With



V2000

PAVA 2000W Power Amplifier  
Mainframe (0 amps Pre  
Installed)

from site

D150

PAVA 150W Power Amplifier  
Module for the V2000 /  
INTEGRA

from site

D500

PAVA 500W Power Amplifier  
Module for the V2000 /  
INTEGRA