zenitel

DATASHEET



2340020026

DSP-15 EExmNT 15W - 2x blind plugs

Ex horn speaker, IP66/7, Ex db eb mb IIB+H2 T4 Gb, 2x Blind plugs

- 15W
- 2x M20 blind plugs
- Tappings: 0.8W - 1.5W - 3W - 4W - 8W - 15W
- Ex db eb mb IIB+H2 T4 Gb
- Ex tb IIIC T105°C Db

IP66 IP67 IEC Ex Intercom Atex

Description

Versatile explosion-proof horn speaker perfectly suited for industrial or maritime environments. Antistatic plastic housing ensures a rugged, yet light-weight construction.

- With a 100V line transformer
- Rated/max. power: 15W
- Tappings: 0.8W - 1.5W - 3.0W - 4.0W - 8.0W - 15.0W
- Material: Antistatic PA / Black
- Bracket and all outside nuts and screws in stainless steel

When mounting the loudspeaker please ensure that it is re-assembled in the same manner in which it was received.

- Fasten bracket with 1-3 screws.
- To change the position of the loudspeaker, please adjust the standard U- bracket (by loosening/tightening the screws) as required.
- For optimum performance, always use the correct voltage/power and operate within the frequency limits as stated.
- Use only certified/specified cable glands and blanking plugs.
- Do not open the loudspeaker when energized.
- Fasten the lid with a torque of 2 - 3 Nm


www.zenitel.com info@zenitel.com


Last revision date: 2026-03-11 08:44


Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.


ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

Technical Dimensions









Primary nominal tappings	
1:2	15,0 W
2:3	8,0 W
3:4	4,0 W
1:3	3,0 W
2:4	1,5 W
1:4	0,8 W

www.zenitel.com info@zenitel.com Last revision date: 2026-03-11 08:44

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

Specifications

GENERAL

Material / Color	Anti-static PA / Black
Mounting	Bracket
Termination	e-chamber, push terminals
Weight w/ transformer	2,2 kg
IP-rating	IP-66/67
Max / min amb temp.	50°C / -50°C
Rated / max. power	15 W / 30 W
SPL 1W/1m	105 dB
SPL rated power	116 dB
Effective freq range	380-7000 Hz
Dispersion (-6dB) 1kHz / 4kHz	200° / 50°
Directivity factor, Q (1kHz)	1,8
Fuse	Thermal fuse- 84°C, 2x Short-circuit protection fuses
Environmental Condition	Exposed

www.zenitel.com info@zenitel.com Last revision date: 2026-03-11 08:44

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.