

2131000141

CL-135T-W/FD

5" Ceiling miniature speaker, 100V, 6W w/fire dome



- ✓ 100V
- ✓ 6W
- ✓ 2x M20 cable glands
- ✓ Steel fire dome


Description

5" miniature speaker for small rooms or where space for mounting speakers is limited.


The speaker has a robust, yet discreet design and installation is easy with two spring clamps.

Technical Dimensions

Item:2131000141 (with steel fire dome)



Item:2131000132 (without steel fire dome)



Specifications

GENERAL

Dimensions (Diameter x Depth)	Ø135 x D82mm
Cut Out Dimension (Dia.)	Ø106
Mounting	Flush mounted – ceiling or wall by spring clamp
Operating temperature range	-20 ~ + 70
Rated Power	6W
Max Power	10W
Sensitivity	80 dB ± 3dB , 1W/1M at 400,500,600,700 Hz-Avg.
Frequency Range	75 Hz ~ 18 KHz -10dB / ±20% Hz
Rated Voltage	100 V
Power tappings	6-3-1.5W
Termination	Ceramic Terminal Block With thermal fuse
Baffle Material	Steel , RAL 9010
Mesh Grille	Steel , RAL 9010
Weight	0,52 kg
Environmental Condition	Protected