



2640500025

Splitter, 2-Way, 380-2700 MHz, APS-02-WBS-LP-NF-CC


Power Splitter

- Amphenol Power Splitters covers the bands of 380 2700 MHz
- PIM value of -153dBc
- Average max power of 300 W
- ✓ IP 65 rating
- N-Female Connector configurations

Description

The Splitter, 2-Way, 380-2700 MHz, APS-02-WBS-LP-NF-CC covers the bands of 380 - 2700 MHz with a PIM value of -153dBc. It has an average max power of 300 W. The splitter is mechanically sound and robust which will allows it to be utilized indoors and outdoors with a IP65 rating. It has connector configurations of N-Female.

Technical Dimensions



Specifications

ELECTRICAL

Frequency	380 - 2700 MHz
Max. Power Input	300 W
Insertion Loss	0.22 dB
Impedance	50 Ω
Peak Input Power	1.5 kW
Passive Intermodulation	< -153 dBc (2 x 43 dBm)
Split Loss	3 dB
No. of Channels	2
Application	Indoor/Outdoor
VSWR	< 1.25:1

MECHANICAL

Connection(s)	N(f)
Color	Black
Weight	0.48kg
RoHS Compliant	Yes
Mounting	3.2 mm dia. (four holes)

ENVIRONMENTAL

Operating Temperature Range	-35°C to +70°C
Humidity	< 95%
Ingress Protection	IP65

page 2/2