

loudspeaker

tbd

SPCM-25W-50-EN54

2 WAY FLUSH MOUNT CEILING SPEAKER

- ✓ EN 54-24 CERTIFIED
- ✓ SIZE 5" (130 MM) CHASSIS AND SEPARATE TWEETER
- ✓ HIGH QUALITY AUDIO FOR VOICE AND BACKGROUND MUSIC
- ✓ 25W / 100V
- ✓ 2 WAY FLUSH MOUNT CEILING SPEAKER
- ✓ FLUSH MAGNETIC FASTENING GRILLE
- ✓ EASY MOUNT CLAMPS
- ✓ IMPACT RESISTANT ABS



Public Address



Voice Alarm

Commercial Audio

EN54

EN 54 Certified

Description

The SPCM-25W-50-EN54 is a 25W 100V 2-way ceiling loudspeaker fitted with a fire dome for voice alarm applications. It has a 5" (130mm) loudspeaker chassis with a high quality tweeter providing excellent sound quality for speech and background music. Certified to EN 54-24 the speaker is fitted with a 100V transformer with three power level adjustment tapings of 25W, 12.5W and 6.25W. Low impedance operation is also possible.

The impact-resistant ABS housing in RAL 9016 guarantees long-term stability. For additional reliability, a thermal fuse is provided. The speaker is protected to class IP 21C and the speaker chassis is treated against damp.

Easy installation is made possible through a simple screw mounting system. Using a magnetic fastening, the finely perforated speaker grille can be removed quickly for access or it can be easily replaced by a different coloured grille, even after installation.

Used With



from site

D150

PAVA 150W Power Amplifier
Module for the V2000 /
INTEGRA

from site

D500

PAVA 500W Power Amplifier
Module for the V2000 /
INTEGRA

V2000

PAVA 2000W Power Amplifier
Mainframe (0 amps Pre
Installed)