



tbd

SPCS-10W-65-EN54

SURFACE MOUNT CEILING SPEAKER

- ✓ Ceiling Loudspeaker
- ✓ 10W 100V
- ✓ Size 6.5" (165mm)
- ✓ Surface mount
- ✓ Quick and easy mounting
- ✓ Full range sound quality
- ✓ Option with DC capacitor fitted
- ✓ Certified to EN 54-24



Public Address



Voice Alarm

Commercial Audio

EN54

EN 54 Certified

Description

The SPCS-10W-65-EN54 is a 10W 100V surface mount ceiling loudspeaker, which has a 6.5" (165mm) full-range chassis providing excellent sound quality with speech and background music. The loudspeaker is fully certified to EN 54-24. The loudspeaker is fitted with a 100V transformer which has four power adjustment tappings of 10W, 6W, 3W and 1.5W.

The SPCS-10W-65-EN54 has a powder coated metal housing and grille, with the high quality finish giving good long-term protection and resistance to corrosion.

The loudspeaker's housing has environmental ingress protection rated to IP21 and is also vandal and shock-resistant to IK code IK08. As standard the loudspeaker is coloured to match RAL9010 'Pure White', however they can be supplied in any four-digit RAL or NCS colour, as a special order.

The 100V loudspeaker line cabling is connected by means of a two-pin ceramic block. For additional reliability, the

speaker chassis features vibration-damping construction. This speaker is compliant with the British Standard BS 5839, Part 8.

The loudspeaker is optionally available with a DC blocking capacitor fitted, in order to provide compatibility with DC loudspeaker line monitoring systems. The part number for this DC monitoring compatible version is SPCS-10W-65-EN54-DC.

Enhanced Acoustic Simulator for Engineers (EASE) data for this loudspeaker is available on request.

Used With



from site

from site

D150

PAVA 150W Power
Amplifier Module for the
V2000 / INTEGRA

D500

PAVA 500W Power
Amplifier Module for the
V2000 / INTEGRA

V2000

PAVA 2000W Power
Amplifier Mainframe (0
amps Pre Installed)