


tbd

SPRS-W-06W-65

SURFACE MOUNT SPEAKER



- ✓ HIGH QUALITY AUDIO FOR VOICE AND BACKGROUND MUSIC
- ✓ SURFACE MOUNT SPEAKER
- ✓ 6W / 100V
- ✓ 6.5" (165mm) FULL RANGE CHASSIS
- ✓ HIGH DENSITY SHOCK RESISTANT MDF WOOD HOUSING

 Public Address  Voice Alarm Commercial Audio

Description

The SPRS-W-06W-65 is a 6W 100V surface mount loudspeaker which has a 6.5" (165mm) full-range chassis providing excellent sound quality with speech and background music. The speaker is fitted with a 100V transformer which has three power adjustment tapings of 6W, 3W and 1.5W.

The SPRS-W-06W-65 has a high-density shock-resistant MDF wood housing which provides a low-resonance sound. The enclosure is ingress protection rated to IP54, and is coloured white. Surface mounting to a wall or ceiling is simply provided through the use of fixing screws, with the enclosure front attaching to the rear mounting panel with spring clips. The 100V loudspeaker line cabling is connected by means of a two-pin ceramic block, and for additional reliability a thermal fuse is provided and the speaker chassis is damp-resistant.

Used With



from site

D150

PAVA 150W Power Amplifier
Module for the V2000 /
INTEGRA

from site

D500

PAVA 500W Power Amplifier
Module for the V2000 /
INTEGRA

V2000

PAVA 2000W Power Amplifier
Mainframe (0 amps Pre
Installed)