

loudspeaker

tbd

# SPCP-16W-50-EN54

## PENDANT CEILING SPEAKER

- ✓ EN 54-24 CERTIFIED
- ✓ HIGH QUALITY AUDIO FOR VOICE AND BACKGROUND MUSIC
- ✓ PENDANT CEILING SPEAKER
- ✓ 16W /100V
- ✓ 5" (130mm) FULL RANGE CHASSIS
- ✓ INGRESS PROTECTION IP35
- ✓ UV-RESISTANT ABS HOUSING RATED TO UL94-HB



Public Address



Voice Alarm

Commercial Audio



EN 54 Certified

## Description

The SPCP-16W-50-EN54 is a 16W 100V pendant ceiling mount loudspeaker, which has a 5" (130mm) fullrange chassis providing excellent sound quality with speech and background music, and which is certified to EN54-24. The speaker is fitted with a 100V transformer which has three power adjustment tappings of 16W, 8W and 4W.

The SPCP-16W-50-EN54 has a powder coated metal chassis and grille, with the high quality finish giving good longterm protection and resistance to corrosion. The speaker has a sturdy, UV-resistant ABS housing rated to UL94-HB, with an ingress protection rating of IP35, and is coloured to match RAL9010 'Pure White'. However, the speakers can be supplied in any four digit RAL or NCS colour, as a special order.

The 100V loudspeaker line connection is provided via a 4.5m long 4core cable, which is terminated to the 100V loudspeaker line site cabling using a two-pin ceramic block, housed within the speaker's ceiling mounting rose. For additional reliability a thermal fuse is provided and the speaker chassis is damp-resistant.

The loudspeaker is optionally available with a DC blocking capacitor fitted, in order to provide compatibility with DC loudspeaker line monitoring systems. The part number for this DC monitoring compatible version is SPCP-16W-50-EN54-DC

## Used With



from site

D150

PAVA 150W Power Amplifier  
Module for the V2000 /  
INTEGRA

from site

D500

PAVA 500W Power Amplifier  
Module for the V2000 /  
INTEGRA

V2000

PAVA 2000W Power Amplifier  
Mainframe (0 amps Pre  
Installed)