



2211200130

Headset for DECT handset V2

Headset

- Bluetooth 4.2 including MultiPoint
- New noise cancelling water resistant speech microphone
- Improved speech intelligibility
- IP68

Description

The Headset for DECT Handset v2 brings many improvements and new exciting features that can help improve the safety and efficiency in critical communication. Level-dependent technology for ambient listening can help you to hear important sounds from the surroundings. With the new feature Push-To-Listen, PTL, you can communicate face-to-face with people standing close by a noisy environment without being tempted to remove your hearing protection.

Bluetooth connectivity for seamless connection to external devices. Support for Bluetooth Multipoint for simultaneous connection of 2 phones (selectable in Set-up mode).

The Headset for DECT Handset v2 is useful when users need to be connected to their mobile device everywhere critical communication and hearing protection is required.

www.zenitel.com

info@zenitel.com

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

Specifications

GENERAL SPECIFICATIONS

Attachment wire	Stainless steel
Two-point fastener	Acetal
Operating temperature	-20°C to +50°C (battery dependent)
Operating time	Approximately 45 hours of battery lifetime with included alkaline batteries
Bluetooth Version	4.2+EDR
Bluetooth Frequency	2400-2483.5 MHz
Supported profiles	HF/HS version 1.5, A2DP version 1.2
Output power	2,5 mW
Menu Language	English
Recommended storage conditions	-20º C - +50º C, <90% humidity
Recommended max. shelf life	5 years except the batteries, <1 year

www.zenitel.com

info@zenitel.com

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.