

2220012274 C1300-48P-4G

Cisco C1300 48-port 1G PoE switch with 4x1G SFP





CISCO Certified

Description

The Cisco Catalyst 1300 Series Switches are fixed, managed, enterprise-class Gigabit Ethernet Layer 3 switches designed for small and medium-sized business and branch offices. These simple, flexible, and secure switches are ideal for deployment out of the wiring closet. The Catalyst 1300 Series operates on customized Linux OS software, with an intuitive dashboard that simplifies network setup and advanced features that accelerate digital transformation, while pervasive security protects business-critical transactions. The 1300 Series switches provide the ideal combination of affordability and capabilities for branches and growing networks and help you create a more efficient, better-connected workforce. When your business needs advanced networking features and security for the digital transformation, yet value is still a top consideration, you're ready for the Cisco Catalyst 1300 Series Switches.

Cisco Catalyst C1300-48P-4G is managed 48-port PoE switch with 48 auto-sensing 10/100/1000 PoE ports and 4x Gigabit Ethernet SFP ports .

page 1/3

www.zenitel.com

info@zenitel.com

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

Specifications

PORTS

10/100/1000 RJ45	48
SFP	4
Console ports	1x RJ45 and USB type C Port

ENVIRONMENT

Operating temperature	-5°to 50°C
Operating relative	10% to 90%, relative, non-
humidity	condensing

ELECTRICAL CHARACTERISTICS

Frequency	50 to 60 Hz
Maximum heat dissipation	1537.68 BTU/hr
AC voltage	100 to 240 VAC
Available PoE Power	370W
Maximum power Consumption	110V = 450.65W
	220V = 437.14W

DIMENSIONS & WEIGHT

Dimensions (W x D x H)	445 x 350 x 44 mm
Weight	5.43 kg
Mounting	Rack Mountable, 1HU

Accessories

www.zenitel.com

info@zenitel.com

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.









Cisco 1000Base-SX SFP Transceiver Module for MultiMode Fiber - IEC60945 Compliant



GLC-LH-SMD

Cisco 1000BASE-LX/LH SFP for Both Multimode and Single-Mode Fibers



1000BASE-LX SFP transceiver Single-mode for SF300 and SF302

MGBSX1

1000BASE-SX SFP transceiver Multimode for SF300 and SF302



GLC-TE

Cisco GLC-TE 1000BASE-T 1G SFP Transceiver - RJ45

page 3/3

www.zenitel.com

info@zenitel.com

Carticle and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.