zenitel

DATASHEET

2220012276

C1300-24FP-4X

Cisco C1300 24-port 1G Full PoE switch with 4x10G SFP+



CISCO Certified

Description

The Cisco Catalyst 1300 Series Switches are fixed, managed, enterprise-class Gigabit Ethernet Layer 3 switches designed for small and medium-sized business and branch offices. These simple, flexible, and secure switches are ideal for deployment out of the wiring closet. The Catalyst 1300 Series operates on customized Linux OS software, with an intuitive dashboard that simplifies network setup and advanced features that accelerate digital transformation, while pervasive security protects business-critical transactions. The 1300 Series switches provide the ideal combination of affordability and capabilities for branches and growing networks and help you create a more efficient, better-connected workforce. When your business needs advanced networking features and security for the digital transformation, yet value is still a top consideration, you’re ready for the Cisco Catalyst 1300 Series Switches.

Cisco Catalyst C1300-24FP-4X is managed 24-port Full PoE switch with 24 auto-sensing 10/100/1000 PoE ports and 4x 10G SFP+ ports .

www.zenitel.com info@zenitel.com Last revision date: 2024-09-17 14:05

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company’s Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

Specifications

PORTS	
10/100/1000 RJ45 PoE+	24
SFP+	4
Console ports	1x RJ45 and USB type C Port

ENVIRONMENT	
Operating temperature	-5°to 50°C
Operating relative humidity	10% to 90%, relative, non-condensing

ELECTRICAL CHARACTERISTICS	
Frequency	50 to 60 Hz
Maximum heat dissipation	1548.8 BTU/hr
AC voltage	100 to 240 VAC
Available PoE Power	370W
Maximum power Consumption	110V = 454.2W
	220V = 441.2W

DIMENSIONS & WEIGHT	
Dimensions (W x D x H)	445 x 345 x 44 mm
Weight	4.92 kg
Mounting	Rack Mountable, 1HU

Accessories

www.zenitel.com info@zenitel.com Last revision date: 2024-09-17 14:05

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.



SFP-10G-SR

CISCO 10GBase-SR SFP+ 10GbE transceiver module for Multimode fiber

Item Number: 2220012153



SFP-10G-LRM

CISCO 10GBase-LRM SFP+ 10GbE transceiver module for both multimode and single-mode fibers

Item Number: 2220012154

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.