



2131000158

CAR-6T-MED

Wall double faced speaker, 100V, IP30, 6W

- I00V line
- 🕗 6W
- IP30
- MED Approved



MED Certification

Description

- Ouble faced loudspeaker w/ transformer for accommodations area
- Ideal for P.A. intercom and background music
- To be used together with 100V line amplifier

The CAR-6T-MED is a general purpose loudspeaker to be used on 50/100 V lines. The speaker is bidirectional and disperses audio in both directions. This feature makes this speaker very well suited for corridors and other applications where audio has to be evenly distributed.

Installation, Operation and Maintenance Procedures

- Fasten loudspeaker with two screws through foot bracket.
- Select required tapping and connect with a suitable terminal.

www.zenitel.com

info@zenitel.com

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

- For optimum performance, always use the correct voltage / power and operate within the frequency limits as stated.
- O not open loudspeaker when energized.
- ⊘ This loudspeaker is supplied with two years warranty against defective workmanship.
- ✓ Temperature fuse is internal installed at the transformer.

www.zenitel.com

info@zenitel.com

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

Specifications

GENERAL

Material / Color	Aluminium / Anodized
Dimensions	175mm x 175mm x 152mm
Mounting	Foot bracket
Termination	Cable, 1m
Weight	1.9 kg
Rated power	6W
SPL 1W / 1 m	90 dB
SPL rated power	96 dB
Effective frequency range	150-20000 Hz
Dispersion (-6dB) 1kHz / 4kHz	360° / 2x60°
Protection	IP30
Environmental Condition	Protected

www.zenitel.com

info@zenitel.com

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.