zenitel

DATASHEET



2131000159

HP-6CT-MED

Mini Horn Loudspeaker, 6W, 100V, IP67

- Suitable for outdoor and indoor installation
- IP67
- EN 45545-2 compliant
- 70V / 100V
- Tappings: 0.5W - 1.5W - 3W - 6W
- MED Approved

MED Certification | Onboard communication | IP67

Description

The HP-6CT-MED is a compact 6 W horn speaker delivering a powerful 100 dB SPL at 1W/1m. Built from durable UL94 V0 polyamide and rated IP67, it ensures reliable performance in harsh indoor and outdoor environments. With a frequency range of 300–20000 Hz, wide dispersion, and a robust mounting bracket, the HP-6CT-MED is ideal for public address, safety, and industrial communication systems.

Installation, Operation and Maintenance Procedures

- Remove the lid and lead cable through the cable gland.
- Connect to terminal 70V: white-green or 100V: white-red.

www.zenitel.com info@zenitel.com


Last revision date: 2026-07-08 15:06

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

- Select the required power by changing the position of the black wire connected to the transformer; choose according to the label inside the loudspeaker.
- Fasten bracket with 1-3 screws.
- Fasten the lid with a torque of 1.5 Nm.
- To change the loudspeaker's position, please adjust the bracket (by loosening/tightening the screws) as required.
- For optimum performance, always use the correct voltage/power and operate within the frequency limits as stated.

Technical Dimensions



70/100 Volt combined transformer	
Primary connections	
White : Green	70 V
White : Red	100 V
Secondary nominal tappings	
C : 6W	6,0 W
C : 3W	3,0 W
C : 1,5W	1,5 W
C : 0,5W	0,5 W

www.zenitel.com info@zenitel.com Last revision date: 2026-07-08 15:06

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

Specifications

GENERAL

Rated power	6 W
SPL 1W / 1 m	100 dB
SPL rated power	107 dB
Effective frequency range	300 - 20000 Hz
Dispersion (-6dB) 1kHz / 4kHz	178° / 62°
Enclosure material / Color	PA - (V0) / RAL 7035
Mounting material	Plastic bracket
Dimensions	Ø97 x 132D mm
Termination	Spring clamp
Connection	1x M20 cable gland, 1x M20 blanking plug
M20 cable gland sealing range	5 - 12 mm
Weight	0.62 kg
IP-rating	67
Max. / min. ambient temperature	110°C / -40°C
Thermal protection	Integrated thermal fuse
Environmental Condition	Exposed

www.zenitel.com info@zenitel.com Last revision date: 2026-07-08 15:06

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.