

2131000162

HP-30T-MED

Horn Loudspeaker, 100V, IP67, 30W



- ✓ Horn Loudspeaker for open deck and machinery spaces.
- ✓ Excellent for P.A. / Intercom
- ✓ With transformer for 100V amplifier line
- ✓ 2x M20 cable gland (7-14mm)
- ✓ Fuse
- ✓ MED Approved



MED Certification



IP66



IP67

Description

- ✓ Wall loudspeaker for accommodation use.
- ✓ Excellent for P.A. intercom and background music
- ✓ With fuse and transformer for 100V amplifier line

Installation, operation and maintenance procedure:

- ✓ When mounting the loudspeaker please ensure that it is re-assembled in the same manner in which it was assembled. Fasten bracket with 1-3 screws.
- ✓ To change the position of the loudspeaker please adjust the bracket (by loosening / tightening the screws) as required.
- ✓ For optimum performance, always use the correct voltage / power and operate within the frequency limits as stated.
- ✓ Do not open loudspeaker when in use

✓ Fasten lid with a torque of 2 - 3 Nm.

Specifications

GENERAL

Dimensions (mm)	237Ø x 298D
Weight	2.2 kg
Mounting	Bracket
Material / Color	Polyamide / RAL 7035
Temperature range	Max. / min. amb. temp 90°C / -40°C
Max. / min. ambient temperature	150 °C / -50 °C
Connections	Internal screw connections
Rated / max. power	30W / 40W
SPL 1W/1m	110dB
SPL rated power	124dB
Effective freq.range	310 – 8000 Hz
Dispersion (-6dB)1kHz / 4kHz	115° / 30°
Environmental Condition	Exposed