



2810011078

CAB-AVT-W-115-230

Active ventilation for CABxx with glass door, 115-230VAC


- ✓ A fan in the cabinet top (Top fan unit 550x340x42mm 280m³/h)
- ✓ Enclosure internal thermostat
- ✓ Thermostat Mounting plate
- ✓ Air inlet
- ✓ IP20

Description


CAB-AVT-W-115-230 is active ventilation for CABxx with a glazed door. It operates on voltages between 100 V - 240 V, 1~, 50 Hz/60 Hz.

The top ventilation unit is equipped with 2 fan units and ensures 280 m³/h of air throughput.

Technical Dimensions



Product description	
Rated operating voltage	100 V - 240 V, 1~, 50 Hz/60 Hz
Air throughput (unimpeded air flow)	280 m ³ /h
IP protection	IP 20
Weight	4,57kg



Specifications

ELECTRICAL DATA

Rated operating voltage	100 V - 240 V, 1~, 50 Hz/60 Hz
Rated current max.	At 50 Hz: 0.7 A At 60 Hz: 0.69 A
Air throughput, unimpeded air flow	280 m ³ /h

DIMENSIONS & WEIGHT

Roof air outlet dimensions (W x H x D)	550x42x340mm
Air inlet fan dimensions (W x H x D)	255x255x25mm

Used With



CAB15F-V2

Floor cabinet 19" 15HU
600x600x800mm fixed frame



CAB24FW-V2

Floor cabinet 19" 24HU
800x600x1200mm fixed frame



CAB24FWD-V2

Floor cabinet 19" 24HU
800x800x1200mm fixed frame



CAB42F-V2

Floor cabinet 19" 42HU
600x600x2000mm fixed frame



CAB42FW-V2

Floor cabinet 19" 42HU
800x600x2000mm fixed frame



CAB42FWD-V2

Floor cabinet 19" 42HU
800x800x2000mm fixed frame



CAB24F-V2

Floor cabinet 19" 24HU
600x600x1200mm fixed frame



CAB24SW-V2

Floor-mounted 24HU cabinet -
800x1200x600mm (WxHxD)
swing frame



CAB42FD-V2

Floor cabinet 19" 42HU
600x800x2000mm fixed frame



CAB42FWDD

Floor cabinet 19" 42HU
800x1000x2000mm fixed frame