

2220012346

C921-4PLTEGB

Cisco ISR 921 4G LTE/HSPA+ for EU



Description

The Cisco 900 Series ISRs deliver integrated security and threat defense, protecting networks from both known and new Internet vulnerabilities and attacks. These powerful, fixed-configuration routers provide secure broadband and Metro Ethernet and wireless LTE WAN connectivity. Service providers offering both managed Ethernet and wireless LTE WAN services can deploy them in customer locations as CPE. Centralized and remote management capabilities are available through web-based tools and Cisco IOS® Software for full visibility and control of network configurations at the remote site.

The 900 Series ISRs simplify the deployment of Ethernet WAN services, with end-to-end Operations, Administration, and Maintenance (OA&M), Service-Level Agreement (SLA) monitoring and verification, and configuration management.

The Cisco 900 Series ISRs come with a 4-port managed switch, providing LAN ports to connect multiple devices.

Specifications

TECHNICAL SPECIFICATIONS

4x Gigabit Ethernet
(GE) switch ports

2x Gigabit Ethernet
(GE) WAN interface
ports

LTE Bands Supported

* LTE bands 1, 3, 7, 8,
20, 28 * FDD LTE 700
MHz (band 28), 800
MHz (band 20), 900
MHz (band 8), 1800
MHz (band 3), 2100
MHz (band 1), and 2600
MHz (band 7)

ENVIRONMENT

Operating temperature 0° to 50°C

Operating relative
humidity 5% to 95%
(noncondensing)

VOLTAGE 100 TO 240 VAC

Frequency 50 to 60 Hz

Electrical
characteristics

DIMENSIONS & WEIGHT

Dimensions (H x W x D) 4.32 x 22.86 x 24.13 cm

Weight 1.2 kg

Mounting bracket
Has to be ordered
separately

Used With



ACS-900-RM-19=

19" Rackmount Kit for
Cisco C921 Router

Item Number: 1015948