zenitel

DATASHEET

1015883

UPS-NRT4-B060

External Battery Module for 5 kVA and 6 kVA UPS Systems, with rail kit



- Compatible with UPS-NRT4-060K unit
- Modular, hot-swappable design for easy maintenance
- EBS (Expert Battery System) optimizes back-up time availability and battery life
- Convertible rack/tower installation
- OBM (Optimized Battery Management) for extended service life

Description

EBM modules are essential on maritime vessels, offshore platforms, and energy facilities where continuous power to critical communication and control systems is vital. They extend UPS runtime for equipment such as PA/GA, intercom, IP telephony, navigation consoles, monitoring systems, and safety infrastructure.


Integrated EBS and OBM systems intelligently manage battery performance to maximize lifespan, maintain stable output during voltage fluctuations, and ensure reliable operation in demanding marine and offshore environments.

Technical Dimensions

www.zenitel.com info@zenitel.com Last revision date: 2026-07-01 12:33

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.



Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

Specifications

GENERAL	
Nominal battery voltage	192 VDC
Battery chemistry type	Sealed lead-acid maintenance free
Battery capacity (Ah)	7 Ah
Number of battery blocks and their configuration	16 x 12 V (Series connection)
Compatible UPS model	UPS-NRT4-060K
Dimensions W x D x H	438 x 600 x 85.5 mm
Weight	40.8 kg
IP Rating	IP20

Used With



UPS-NRT4-060K

Online UPS, 6000W/3min, 230V, w/battery & rails

Item Number: 1015882

www.zenitel.com info@zenitel.com Last revision date: 2026-07-01 12:33

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.