zenitel

DATASHEET





2810011076

CAB-AVF-L-115

Active ventilation for CABxx with a steel door, 115 VAC

- The package consists of:
  - Fan-and-Filter Unit: front-door mounting, 255x255 mm, 115 VAC
  - Internal Thermostat (with mounting plate)
  - Roof Air Outlet (non-powered)
- IP22

Description

The CAB-AVF-L-115 active ventilation package is a cost-effective solution designed for the CABxx series steel-door cabinets. It offers easy installation and simple maintenance, making it suitable for both new and existing enclosures. The fan-and-filter unit supports multiple mounting positions—front, side, or rear—allowing flexible integration based on airflow needs. This package provides reliable airflow management and helps maintain stable operating temperatures inside the different cabinets.


Technical Dimensions

www.zenitel.com info@zenitel.com

Last revision date: 2026-01-16 08:56

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.



www.zenitel.com info@zenitel.com Last revision date: 2026-01-16 08:56

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

Specifications

GENERAL (FAN-AND-FILTER UNIT)

Rated operating voltage	115 V, 1~, 50/60 Hz
Power consumption	At 50 Hz: 35.5 W / At 60 Hz: 38.2 W
Rated current max.	At 50 Hz: 0.41 A / At 60 Hz: 0.42 A
Air throughput, unimpeded airflow (with chopped-fibre filter)	At 50 Hz: 175 m³/h / At 60 Hz: 157 m³/h
Air throughput, unimpeded airflow (with pleated filter)	At 50 Hz: 130 m³/h / At 60 Hz: 112 m³/h
Air throughput with matching outlet filter including pleated filter	At 50 Hz: 191 m³/h / At 60 Hz: 161 m³/h
Pre-fuse	Miniature circuit-breaker/fuse: 4 A
IP protection category to IEC 60 529	IP 54-56 (depending on filter type)
Dimensions W x D x H	255 x 129 x 255 mm
Installation depth	108 mm
Weight	2.381 kg

GENERAL (INTERNAL THERMOSTAT)

Rated operating voltage	24-230 VAC, 1~ / 24-60 VDC
Dimensions W x D x H	71 x 33.5 x 71 mm
Weight	0.12 kg

GENERAL (ROOF AIR OUTLET)

Dimensions W x D x H	559 x 37 x 459 mm
IP Protection	IP22

Used With

www.zenitel.com info@zenitel.com Last revision date: 2026-01-16 08:56

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.



CAB42F-V2

Floor cabinet 19" 42HU
600x600x2000mm fixed frame

Item Number: 2810010113



CAB42FW-V2

Floor cabinet 19" 42HU
800x600x2000mm fixed frame

Item Number: 2810010114



CAB42FWD-V2

Floor cabinet 19" 42HU
800x800x2000mm fixed frame

Item Number: 2810010115



CAB42SWD-V2

Floor cabinet 19" 42HU
800x800x2000mm swing frame

Item Number: 2810010120



CAB42FD-V2

Floor cabinet 19" 42HU
600x800x2000mm fixed frame

Item Number: 2810010121



CAB42FWDD

Floor cabinet 19" 42HU
800x1000x2000mm fixed frame

Item Number: 2810010123

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.