

EOL10K / LBC2W to LBC63W

End-Of-Line Terminator and Line Blocking Capacitor Kits



The EOL10K is a close tolerance, high stability "End-Of-Line" power resistor, for use with the "DC line monitoring" feature integral to the LSZDC and LSDDC interface cards.

The LBC2W to LBC63W are suitably rated line blocking capacitor kits for fitting to each loudspeaker on the line. These are required for DC loudspeaker line monitoring.

The EOL10K and LBCxxW products are intended for installation into third party loudspeaker enclosures or "junction boxes", and are therefore supplied as small radial leaded devices for ease of installation. Alternatively many loudspeaker suppliers will fit LBCxxWs as part of the original equipment supply.

For further details please refer to the EOL10K / LBC2W to LBC63W product manual, the Amplifier Mainframe manual, and the Application Solutions PA/VA Systems Design Handbook.

For details of other products please visit www.asl-control.co.uk

Specification

EOL10K

3 Watt 10K 1% 20PPM drift per degree centigrade

LBCs

10% 250V DC polyester capacitors



This equipment is designed and manufactured to conform to the following EC standards:

EMC EN 55103-1 Environment E1, EN 55103-2 Environment E5

Safety EN 60065

Failure to use the equipment in the manner described in the product literature will invalidate the warranty.

A 'Declaration of Conformity' statement to the above standards, and a list of auxiliary equipment used for compliance verification, is available on request.

Manufacturer

Application Solutions (Safety and Security) Limited

Unit 17 – Cliffe Industrial Estate - Lewes - East Sussex – BN8 6JL – U.K.

Tel: +44(0)1273 405411 Fax: +44(0)1273 405415

www.asl-control.co.uk



QUALITY ASSURED FIRM
CERTIFICATE NUMBER 96109-AQ-041

All rights reserved.

Information contained in this document is believed to be accurate, however no representation or warranty is given and Application Solutions Limited assumes no liability with respect to the accuracy of such information.