



## WMC01

# Wall mount source selector and volume controller. Designed for usability and precise control.

The WMC01 allows the users to select from a list of different music channels, input a local audio source and or adjust broadcast volumes within an ASL system. Making it the perfect choice for both commercial or industrial installations; such as restaurants, meeting rooms, executive boxes and hotel lobbies. Operation is simple and intuitive; The vertical arrows allow the user to switch between source select and volume control modes, and the horizontal arrows are used to change between sources and adjust the broadcast volume. A standard 3.5mm socket allows an audio device such as phone or music player to be connected locally, this input can be disabled in configuration if required. Connections can be made over either Ethernet with power sourced from a PoE supply or via a direct serial / analogue audio link with power sourced from the ASL system. The device includes a back box to make installation simple, and is available as standard in either black or white finishes.

### Specifications

#### General

| Music Input                     | 3.5mm Jack Unbalanced Stereo                           |  |
|---------------------------------|--|--|
| Serial Connection to ASL System | Analogue Audio / Balanced / 0 dBu<br>Nominal / 220 Ohm |  |
| IP Connectivity                 |  |  |
| Audio and Control Protocol      | PMC & VIPA   |  |
| Audio Data                      | TCP IP / Layer 2&3 / Multicast                         |  |
| Control Data                    | TCP IP / Layer 2&3 / Unicast                           |  |
| Ethernet Port                   | 1x RJ458 Copper 100BASE-T                              |  |
| Mechanical                      |  |  |
| Dimensions                      | 195mm (h) x 138mm (w) 50mm (d)                         |  |
| Weight                          | 610g   |  |
| Ingress Protection              | IP30   |  |
| Mounting Options                | Wall Mount (Flush Mount)                               |  |
| Colour Options                  | Black or White   |  |
| Finish                          | Plastic case   |  |

#### **Power Supplies**

| PoE               | 42 - 57V DC |
|-------------------|-------------|
| DC Input Voltage  | 15 - 40V DC |
| Power Consumption | 2.5W        |
|                   |             |

#### Environmental

| Temperature (Operational) | -5°C to +40°C            |
|---------------------------|--------------------------|
| Temperature (Storage)     | -5°C to +50°C            |
| Humidity                  | 0% to 93% non-condensing |

#### **Approval and Standard Compliance**

| Environmental Directive (Safety) | EN60065   |
|----------------------------------|---|
| Environmental Directive          | EN 55103-1/E1 / EN 55103-2/E5 / EN 50121-4 / ENV50204 |
| Environmental                    | RoHS / REACH  |
|                                  |   |

#### **Part Codes**

| WMC01-W White Version | WMC01-B | Black Version |
|-----------------------|---------|---------------|
|                       | WMC01-W | White Version |

#### **Compatible Products**

VIPEDIA - Range INTEGRA - Range

Information contained in this document is believed to be accurate, however no representation or warranty is given and Application Solutions (Safety and Security) Limited assumes no liability with respect to the accuracy of such information. Data subject to change without notice © Application Solutions (Safety and Security) Limited 2021. All rights reserved. Version: 9 May 2021







