

- **FLUSH MOUNT**
- **4 BUTTON**
- **STAINLESS STEEL**
- **GOOSE NECK**
- **PAGING MICROPHONE**



OVERVIEW

The VRMS4-C1 is a flush desk mounting microphone console with a flexible goose neck.

It is a long life, robust and spill proof unit which is designed to work with ASL's range of voice alarm and public address products. The unit is powered via nominal 24V DC.

- Four zone selection buttons with *Busy* and *Select* LED indications.
- A *Press To Talk* button with *Speak Now* LED indication.
- A level indicator showing the peak voice level.

An in-built signal limiting and automatic gain control is provided to help compensate for varying operator technique.

Audio is provided as Balanced Analogue. Mic capsule fault reporting is provided.

CONNECTIONS

Ext. MIC offers connection to optional external microphones.

Ext. PTT offers optional external Press To Talk input.

Analogue audio, power and a serial link (RJ45 connector)

SPECIFICATION

Power Supply

Input 14-40 V DC
 Current consumption (max @ 24V DC)..... 200 mA
 Current consumption (quiescent @ 24V DC) 100 mA

System Connection

Connection RJ45
 Audio Format..... Balanced Analogue Audio

Mechanical

Dimensions (H x W x D mm) 50x247x157(exc. Mic)
 Weight 1.8kg

Environmental

Temperature (Storage) -5 °C to +50 °C
 Temperature (Operation)..... -5 °C to +40 °C
 Humidity Range.....0% to 93% non-condensing



This equipment is designed and manufactured to conform to the following EC standards:

EMC: EN55103-1/E1, EN55103-2/E5, EN50121-4, ENV50204

Safety: EN60065

Application Solutions (Safety and Security) Limited

Unit 17 - Cliffe Industrial Estate - Lewes - East Sussex - BN8 6JL - U.K.

Tel: +44(0)1273 405411

www.asl-control.co.uk



ISO9001 & SO14001

All rights reserved.

Information contained in this document is believed to be accurate, however no representation or warranty is given and Application Solutions (Safety and Security) Limited assumes no liability with respect to the accuracy of such information.