

## NRT4-U015B

# NETYS RT 1.5kVA VFI UPS 1/1 PF=1 WITH BATTERY INTEGRATED +RAILS



### Strong points

- Best-in-class design
- Up to 5-year warranty
- Ease of use
- Optimum battery management
- IoT and cybersecurity
- Simple installation within any operating environment
- Li-Ion battery UPS: Compact and resilient
- Li-Ion battery UPS: Faster and longer

### General characteristics

- Rack/Tower convertible.
- Embedded dry-contact interface.
- Input/Output cables (1000-3000 VA).
- Rail kit and rack ears.
- USB cable.
- Tower stands.
- Cable lockers.
- Connection for battery extension modules.
- Port for parallel operation (5000 - 10000 VA).
- Internal temperature sensor.
- Power off the UPS remotely.
- Cold start.
- Auto and Manual battery test.

### Compliance with standards

- IEC 62040-1
- IEC 62040-2
- IEC 62040-3
- AS 62040.1.1
- AS 62040.1.2
- AS 62040.2
- RCM (E2376)

### Link to the reference



<https://emea.socomec.com/en/reference/NRT4-U015B>

NETYS RT is the fourth generation of single-phase rack-tower UPS, ensuring the protection and availability of IT infrastructure that meets the demands of both power reliability and installation flexibility.

<b>Classification</b>	
UNSPSC	39121011
ETIM Class	EC000382
IGCC	4149
<b>Commerce</b>	
Description	NeTYS RT 1500VA VFI UPS 1/1 PF=1 WITH BATTERY INTEGRATED +RAILS
Effective date	2025-01-01
Offer Life Cycle Code	40
<b>Environmental Sustainability</b>	
Climate change - Total - Cradle to Grave [kg CO <sub>2</sub> eq.]	2722
Climate change - Total - Cradle to Gate [kg CO <sub>2</sub> eq.]	130
<b>ETIM - Electrical characteristics</b>	
Input voltage [V]	110..300
Primary frequency [Hz]	40..70
Number of phases primary	1
Output voltage [V]	200..240
Secondary frequency [Hz]	50..60
Output effective power [W]	1500
Output apparent power [VA]	1500
Number of phases secondary	1
SNMP	No
Voltage type	AC
Max. voltage distortion output (linear load) [%]	1
Output power factor	1
<b>ETIM - Mechanical characteristics</b>	
Height [mm]	85.5
Width [mm]	438
Depth [mm]	445
Weight [kg]	15.7
Construction type	482.6 mm (19 inch) device
Input connection	C14
Number of output connections C13	8
<b>ETIM - Technical features</b>	
USB interface	Yes
With communication interface RS-232	No
Bridging time full load [min]	3
Suitable for network-management	Yes
USV- technology	Online
Overall efficiency [%]	91.4
Efficiency in eco-mode [%]	97.3

Potential free switch contact	Yes
Auto shut down function	Yes
<b>Logistics</b>	
GTIN/EAN	8027122823395
Customs number	8504409590
Price unit	PC
Weight of the packing unit [kg]	21.3
Length of the packing unit [m]	0.5
Width of the packing unit [m]	0.24
Depth of the packing unit [m]	0.59
<b>Norms</b>	
Conformity to standards	IEC
<b>Technical Characteristics</b>	
Height [mm]	85.5
Width [mm]	438
Depth [mm]	445
Weight [kg]	15.7
In/out	1/1
Output voltage	230
Rated frequency	50/50
Sn [kVA]	1.5
Pn [kW]	1.5
Conf	C1
Input voltage	230
Rate (min)	1.5
Rate (max)	1.5
Life Time	03-05
Typical Backup Time [min]	8
Configuration	UPS Single Unit(s) with Bypass