





|   |   |
|---|---|
| <p><b>TEST REPORT</b></p> <p><b>IEC 60950-1</b></p> <p><b>Information technology equipment – Safety –</b></p> <p><b>Part 1: General requirements</b></p>  |   |
| <b>Report Number</b> .....  | <b>303846</b>   |
| <b>Date of issue</b> .....  | 2016-02-25  |
| <b>Total number of pages</b> .....  | 41  |
| <b>Applicant's name</b> .....   | Ascom Sweden AB   |
| <b>Address</b> .....  | Grimbodalen 2, SE-402 76 Göteborg, Sweden                 |
| <b>Test specification:</b>  |   |
| <b>Standard</b> .....   | IEC 60950-1:2005 (Second Edition) + Am 1:2009 + Am 2:2013 |
| <b>Test procedure</b> .....   | CB Scheme   |
| <b>Non-standard test method</b> .....   | N/A   |
| <b>Test Report Form No.</b> .....   | IEC60950_1F   |
| <b>Test Report Form(s) Originator</b> .....   | SGS Fimko Ltd   |
| <b>Master TRF</b> .....   | Dated 2014-02   |
| <p><b>Copyright © 2014 IEC System of Conformity Assessment Schemes for Electrotechnical Equipment and Components (IECEE System). All rights reserved.</b></p> <p>This publication may be reproduced in whole or in part for non-commercial purposes as long as the IECEE is acknowledged as copyright owner and source of the material. IECEE takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.</p> <p><b>This report is not valid as a CB Test Report unless signed by an approved CB Testing Laboratory and appended to a CB Test Certificate issued by an NCB in accordance with IECEE 02.</b></p> |   |
| <b>General disclaimer:</b>  |   |
| <p>The test results presented in this report relate only to the object tested.</p> <p>This report shall not be reproduced, except in full, without the written approval of the Issuing CB Testing Laboratory. The authenticity of this Test Report and its contents can be verified by contacting the NCB, responsible for this Test Report.</p>  |   |

|                                      |   |
|--------------------------------------|---|
| <b>Test item description</b> ..... : | Transmitter   |
| <b>Trade Mark</b> ..... :            | Ascom   |
| <b>Manufacturer</b> .....            | Same as applicant   |
| <b>Model/Type reference</b> ..... :  | H952T/..<br>U952T-A.../..<br>(The symbols "." in model name can be any alphanumeric characters indicating differences not affecting safety) |
| <b>Ratings</b> ..... :               | Max. 2.0A / 12.5VDC ( $\pm 10\%$ ) (H952T/..)<br>Max. 2.5A / 12.5VDC ( $\pm 10\%$ ) (U952T-A.../..)   |

|  |   |  |
|--|---|--|
| <b>Testing procedure and testing location:</b> |   |  |
| <input checked="" type="checkbox"/>            | <b>CB Testing Laboratory:</b>                       | <b>Nemko AS</b>  |
| <b>Testing location/ address .....</b>         |   | Gaustadalléen 30<br>NO-0373 Oslo<br>Norway   |
| <input type="checkbox"/>                       | <b>Associated CB Testing Laboratory:</b>            |  |
| <b>Testing location/ address .....</b>         |   |  |
| <b>Tested by (name + signature).....</b>       |   | Ole Morten Aaslund  |
| <b>Approved by (name + signature).....</b>     |   | Hans-Eirik Lie      |
| <hr/>  |   |  |
| <input type="checkbox"/>                       | <b>Testing procedure: TMP/CTF Stage 1:</b>          |  |
| <b>Testing location/ address .....</b>         |   |  |
| <b>Tested by (name + signature).....</b>       |   |  |
| <b>Approved by (name + signature).....</b>     |   |  |
| <hr/>  |   |  |
| <input type="checkbox"/>                       | <b>Testing procedure: WMT/CTF Stage 2:</b>          |  |
| <b>Testing location/ address .....</b>         |   |  |
| <b>Tested by (name + signature).....</b>       |   |  |
| <b>Witnessed by (name + signature) .....</b>   |   |  |
| <b>Approved by (name + signature).....</b>     |   |  |
| <hr/>  |   |  |
| <input type="checkbox"/>                       | <b>Testing procedure:<br/>SMT/CTF Stage 3 or 4:</b> |  |
| <b>Testing location/ address .....</b>         |   |  |
| <b>Tested by (name + signature).....</b>       |   |  |
| <b>Witnessed by (name + signature) .....</b>   |   |  |
| <b>Approved by (name + signature).....</b>     |   |  |
| <b>Supervised by (name + signature).....</b>   |   |  |
| <hr/>  |   |  |



**Summary of compliance with National Differences:****List of countries addressed**

- 1) All CENELEC members as listed in EN 60950-1:2006 + A11:2009 + A1:2010 + A12:2011 + A2:2013
- 2) Australia / New Zealand – Differences according to online CB bulletin, last modified 2011-05-06
- 3) USA – Differences according to online CB bulletin, last updated 2014-01-24
- 4) Canada - Differences according to online CB bulletin, last updated 2014-09-13

**The product fulfils the requirements of  
EN 60950-1:2006 + A11:2009 + A1:2010 + A12:2011 + A2:2013**

**Copy of marking plate:**

The artwork below may be only a draft. The use of certification marks on a product must be authorized by the respective Certification Bodies that own these marks.



This device complies whit Part 15 of the FCC Rules.  
 Operation is subjected to the following two conditions:  
 (1) this device may cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operations.



This device complies with Part 15 of the FCC Rules.  
 Operation is subjected to the following two conditions:  
 (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Any modifications made to this device that is not approved by the supplier may void the authority granted to the user by FCC to operate the equipment.

This class B digital apparatus complies with Canadian ICES-003.  
 Cet appareil numérique de la Classe B conforme á lanorme NMB-003 du Canada.

|                                |   |
|--------------------------------|---|
| <b>Calibration</b>             | All instruments used in the tests given in this test report are calibrated and traceable to national or international standards.<br>Further information about traceability will be given on request.  |
| <b>Measurement uncertainty</b> | Measurement uncertainties are calculated for all instruments and instrument set-ups given in this report. Calculations are based on the principles given in the standard EA-4/02 (Dec. 1999), IEC Guide 115:2007, Nemko routine L227 and other relevant internal Nemko-procedures.<br>Further information about measurement uncertainties will be given on request.   |
| <b>Evaluation of results</b>   | If not explicitly stated otherwise in the standard, the test is passed if the measured value is equal to or below (above) the limit line, regardless of the measurement uncertainty. If the measured value is above (below) the limit line, the test is not passed - ref IEC Guide 115:2007, and Nemko routine L220. The instrumentation accuracy is within limits agreed by IECEE-CTL (ref. Nemko routine L227). |

|  |  |
|--|--|
| <b>Test item particulars..... :</b>  |  |
| <b>Equipment mobility.....:</b>  | <input type="checkbox"/> movable <input type="checkbox"/> hand-held <input type="checkbox"/> transportable<br><input checked="" type="checkbox"/> stationary <input type="checkbox"/> for building-in <input type="checkbox"/> direct plug-in  |
| <b>Connection to the mains.....:</b>   | <input type="checkbox"/> pluggable equipment <input type="checkbox"/> type A <input type="checkbox"/> type B<br><input type="checkbox"/> permanent connection<br><input type="checkbox"/> detachable power supply cord<br><input type="checkbox"/> non-detachable power supply cord<br><input checked="" type="checkbox"/> not directly connected to the mains |
| <b>Operating condition.....:</b>   | <input checked="" type="checkbox"/> continuous<br><input type="checkbox"/> rated operating / resting time:   |
| <b>Access location .....</b>   | <input checked="" type="checkbox"/> operator accessible<br><input type="checkbox"/> restricted access location   |
| <b>Over voltage category (OVC) .....</b>   | <input type="checkbox"/> OVC I <input type="checkbox"/> OVC II <input type="checkbox"/> OVC III <input type="checkbox"/> OVC IV<br><input checked="" type="checkbox"/> other: Class III equipment  |
| <b>Mains supply tolerance (%) or absolute mains supply values .....</b>                              | +/-10%   |
| <b>Tested for IT power systems .....</b>   | N/A  |
| <b>IT testing, phase-phase voltage (V) .....</b>   | N/A  |
| <b>Class of equipment .....</b>  | <input type="checkbox"/> Class I <input type="checkbox"/> Class II <input checked="" type="checkbox"/> Class III<br><input type="checkbox"/> Not classified  |
| <b>Considered current rating of protective device as part of the building installation (A) .....</b> | N/A  |
| <b>Pollution degree (PD) .....</b>   | <input type="checkbox"/> PD 1 <input checked="" type="checkbox"/> PD 2 <input type="checkbox"/> PD 3   |
| <b>IP protection class .....</b>   | Min. IP20  |
| <b>Altitude during operation (m) .....</b>   | Max. 2000  |
| <b>Altitude of test laboratory (m) .....</b>   | 100  |
| <b>Mass of equipment (kg) .....</b>  | < 1.0<br>Dimensions: 275 mm by 130 mm by 60 mm   |



|   |  |
|---|--|
| <b>Possible test case verdicts:</b><br>- test case does not apply to the test object ..... : N/A<br>- test object does meet the requirement..... : P (Pass)<br>- test object does not meet the requirement..... : F (Fail)  |  |
| <b>Testing..... :</b><br><b>Date of receipt of test item ..... :</b> December 2011 (initial order no. 193634)<br><b>Date (s) of performance of tests ..... :</b> December 2011 – March 2012 (initial order no. 193634)  |  |
|   |  |
| <b>General remarks:</b><br>"(See Enclosure #)" refers to additional information appended to the report.<br>"(See appended table)" refers to a table appended to the report.<br><b>Throughout this report a <input type="checkbox"/> comma / <input checked="" type="checkbox"/> point is used as the decimal separator.</b> |  |

|   |  |
|---|--|
| <b>Manufacturer's Declaration per sub-clause 4.2.5 of IEC60950-1:</b>   |  |
| The application for obtaining a CB Test Certificate includes more than one factory location and a declaration from the Manufacturer stating that the sample(s) submitted for evaluation is (are) representative of the products from each factory has been provided ..... : | <input type="checkbox"/> <b>Yes</b><br><input checked="" type="checkbox"/> <b>Not applicable</b> |
| <b>When differences exist; they shall be identified in the General product information section.</b>   |  |
| <b>Name and address of factory (ies) ..... :</b> Fideltronik Scandinavia AB<br>Box 207, Östergårdsgatan,<br>SE-524 23, Herrljunga,<br>Sweden  |  |

**General product information:**

The equipment under tests is a Terminal transmitter is part of the On-site Paging (OSP) - and Personal Security (PSS) Systems. It operates either in the HF range (H952T/..) or in the UHF range (U952T-A.../..) Output power can be adjusted to comply with regulations of applicable authorities. The transmitter is housed in a 900 module plastic box with a metal heat sink and shield cover at the top. The RF input will connect to an external antenna.

The equipment is wall mounted and provided with screws for mounting.

Installation is done by a service person.

Maximum recommended ambient (Tmra): 55°C

Connection to the supply: Internal screw terminals

**1.1.2 – Additional requirements:**

Exposure to extreme temperatures, excessive dust, moisture or vibration; to flammable gasses; to corrosive or explosive atmospheres:

This equipment is intended to operate in a “normal” environment (Offices and homes).

Electromedical equipment connected to the patient:

This equipment is not an electromedical equipment intended to be physically connected to a patient.

Equipment used in vehicles, ships or aircrafts, in tropical countries, or at elevations > 2000m:

This equipment is intended to operate in a “normal” environment (Offices and homes).

**Abbreviations used in the report:**

|                                      |             |                            |              |
|--------------------------------------|-------------|----------------------------|--------------|
| - normal conditions                  | <b>N.C.</b> | - single fault conditions  | <b>S.F.C</b> |
| - functional insulation              | <b>OP</b>   | - basic insulation         | <b>BI</b>    |
| - double insulation                  | <b>DI</b>   | - supplementary insulation | <b>SI</b>    |
| - between parts of opposite polarity | <b>BOP</b>  | - reinforced insulation    | <b>RI</b>    |

**Indicate used abbreviations (if any)**

| IEC 60950-1 |                    |                 |         |
|-------------|--------------------|-----------------|---------|
| Clause      | Requirement + Test | Result - Remark | Verdict |

|   |                |  |   |
|---|----------------|--|---|
| 1 | <b>GENERAL</b> |  | P |
|---|----------------|--|---|

|            |  |  |     |
|------------|--|--|-----|
| <b>1.5</b> | <b>Components</b>  |  | P   |
| 1.5.1      | General  | -  | P   |
|            | Comply with IEC 60950-1 or relevant component standard   | (see appended tables 1.5.1)  | P   |
| 1.5.2      | Evaluation and testing of components   | <p>Certified components are used in accordance with their ratings, certifications and they comply with applicable parts of this standard.</p> <p>Components not certified are used in accordance with their ratings and they comply with applicable parts of IEC 60950-1 and the relevant component standard.</p> <p>Components, for which no relevant IEC-standard exists, have been tested under the conditions occurring in the equipment, using applicable parts of IEC 60950-1.</p> | P   |
| 1.5.3      | Thermal controls   | No thermal controls.   | N/A |
| 1.5.4      | Transformers   | No isolating transformer in the equipment.   | N/A |
| 1.5.5      | Interconnecting cables   | No interconnecting cables.   | N/A |
| 1.5.6      | Capacitors bridging insulation   | Class III equipment.   | N/A |
| 1.5.7      | Resistors bridging insulation  | Class III equipment.   | N/A |
| 1.5.7.1    | Resistors bridging functional, basic or supplementary insulation                                   | No requirements for functional insulation in SELV circuits.  | N/A |
| 1.5.7.2    | Resistors bridging double or reinforced insulation between a.c. mains and other circuits           | Class III equipment.   | N/A |
| 1.5.7.3    | Resistors bridging double or reinforced insulation between a.c. mains and antenna or coaxial cable | Class III equipment.   | N/A |
| 1.5.8      | Components in equipment for IT power systems   | Class III equipment.   | N/A |
| 1.5.9      | Surge suppressors  | Class III equipment.   | N/A |
| 1.5.9.1    | General  | -  | N/A |
| 1.5.9.2    | Protection of VDRs   | -  | N/A |
| 1.5.9.3    | Bridging of functional insulation by a VDR   | -  | N/A |
| 1.5.9.4    | Bridging of basic insulation by a VDR  | -  | N/A |
| 1.5.9.5    | Bridging of supplementary, double or reinforced insulation by a VDR                                | -  | N/A |

| IEC 60950-1 |                    |                 |         |
|-------------|--------------------|-----------------|---------|
| Clause      | Requirement + Test | Result - Remark | Verdict |

|            |                                      |   |     |
|------------|--------------------------------------|---|-----|
| <b>1.6</b> | <b>Power interface</b>               |   | P   |
| 1.6.1      | AC power distribution systems        | Class III equipment.  | N/A |
| 1.6.2      | Input current                        | See appended table 1.6.2.<br>Results provided for reference only. | P   |
| 1.6.3      | Voltage limit of hand-held equipment | Not hand-held.  | N/A |
| 1.6.4      | Neutral conductor                    | Class III equipment.  | N/A |

|            |  |   |     |
|------------|--|---|-----|
| <b>1.7</b> | <b>Marking and instructions</b>                                |   | P   |
| 1.7.1      | Power rating and identification markings                       | The required marking is located on the outside surface of the equipment.  | P   |
| 1.7.1.1    | Power rating marking   | -   | P   |
|            | Multiple mains supply connections.....:                        | Class III equipment.  | N/A |
|            | Rated voltage(s) or voltage range(s) (V) .....                 | 12.5±10% VDC  | P   |
|            | Symbol for nature of supply, for d.c. only .....               | Marked with DC. (H952T/..)  | P   |
|            | Rated frequency or rated frequency range (Hz) ... :            | DC supplied.  | N/A |
|            | Rated current (mA or A) .....                                  | Max 2.5A (U952T-A.../..)<br>Max 2.0A (H952T/..)   | P   |
| 1.7.1.2    | Identification markings  | Refer below.  | P   |
|            | Manufacturer's name or trade-mark or identification mark ..... | Ascom   | P   |
|            | Model identification or type reference .....                   | U952T-A.../..<br>H952T/..<br>(The symbols "." in model name can be any alphanumeric characters indicating differences not affecting safety) | P   |
|            | Symbol for Class II equipment only .....                       | Class III equipment.  | N/A |
|            | Other markings and symbols .....                               | Ref. Copy of marking plate.<br>Additional markings do not give rise to misunderstanding.  | P   |
| 1.7.1.3    | Use of graphical symbols                                       | Comply with relevant standards.   | P   |
| 1.7.2      | Safety instructions and marking                                | No special precautions are necessary.   | N/A |
| 1.7.2.1    | General  | Considered.   | P   |
| 1.7.2.2    | Disconnect devices   | Disconnect device external to the equipment.  | P   |
| 1.7.2.3    | Overcurrent protective device                                  | Class III equipment.  | N/A |
| 1.7.2.4    | IT power distribution systems                                  | Class III equipment.  | N/A |
| 1.7.2.5    | Operator access with a tool                                    | No hazardous parts within the equipment.  | N/A |

| IEC 60950-1 |  |   |         |
|-------------|--|---|---------|
| Clause      | Requirement + Test   | Result - Remark                                     | Verdict |
| 1.7.2.6     | Ozone  | The equipment does not produce ozone.               | N/A     |
| 1.7.3       | Short duty cycles  | The equipment is intended for continuous operation. | N/A     |
| 1.7.4       | Supply voltage adjustment .....  | No voltage selector.                                | N/A     |
|             | Methods and means of adjustment; reference to installation instructions .....        | -   | N/A     |
| 1.7.5       | Power outlets on the equipment .....   | Class III equipment. No power outlets.              | N/A     |
| 1.7.6       | Fuse identification (marking, special fusing characteristics, cross-reference) ..... | No fuse.  | N/A     |
| 1.7.7       | Wiring terminals   | Refer below.  | N/A     |
| 1.7.7.1     | Protective earthing and bonding terminals.....                                       | Class III equipment.                                | N/A     |
| 1.7.7.2     | Terminals for a.c. mains supply conductors   | Class III equipment.                                | N/A     |
| 1.7.7.3     | Terminals for d.c. mains supply conductors   | Class III equipment.                                | N/A     |
| 1.7.8       | Controls and indicators  | Refer below.  | P       |
| 1.7.8.1     | Identification, location and marking.....  | No controls or indicators affecting safety.         | N/A     |
| 1.7.8.2     | Colours .....  | Only functional indicators use colours.             | P       |
| 1.7.8.3     | Symbols according to IEC 60417.....  | -   | N/A     |
| 1.7.8.4     | Markings using figures .....   | No controls with different positions.               | N/A     |
| 1.7.9       | Isolation of multiple power sources .....  | Class III equipment, only one connection to supply. | N/A     |
| 1.7.10      | Thermostats and other regulating devices .....                                       | No thermostats or other regulating devices.         | N/A     |
| 1.7.11      | Durability   | Marking withstands required tests.                  | P       |
| 1.7.12      | Removable parts  | No marking is placed on removable parts.            | P       |
| 1.7.13      | Replaceable batteries .....  | No batteries.                                       | N/A     |
|             | Language(s) .....  | -   | —       |
| 1.7.14      | Equipment for restricted access locations .....                                      | Equipment not intended for installation in RAL.     | N/A     |

| IEC 60950-1 |                    |                 |         |
|-------------|--------------------|-----------------|---------|
| Clause      | Requirement + Test | Result - Remark | Verdict |

|            |  |   |     |
|------------|--|---|-----|
| <b>2</b>   | <b>PROTECTION FROM HAZARDS</b>   |   | P   |
| <b>2.1</b> | <b>Protection from electric shock and energy hazards</b>   |   | P   |
| 2.1.1      | Protection in operator access areas  | Refer below.  | N/A |
| 2.1.1.1    | Access to energized parts  | 2.1.1.1 – 2.1.1.7; No ELV, TNV or hazardous voltages in the equipment | N/A |
|            | Test by inspection .....   | -   | N/A |
|            | Test with test finger (Figure 2A) .....  | -   | N/A |
|            | Test with test pin (Figure 2B) .....   | -   | N/A |
|            | Test with test probe (Figure 2C) .....   | -   | N/A |
| 2.1.1.2    | Battery compartments   | -   | N/A |
| 2.1.1.3    | Access to ELV wiring   | -   | N/A |
|            | Working voltage (V <sub>peak</sub> or V <sub>rms</sub> ); minimum distance through insulation (mm) | -   | —   |
| 2.1.1.4    | Access to hazardous voltage circuit wiring   | No hazardous voltages in the equipment.                               | N/A |
| 2.1.1.5    | Energy hazards .....   | No energy hazard in operator access area.                             | N/A |
| 2.1.1.6    | Manual controls  | No shafts or knobs.   | N/A |
| 2.1.1.7    | Discharge of capacitors in equipment   | Class III equipment.  | N/A |
|            | Measured voltage (V); time-constant (s) .....  | -   | —   |
| 2.1.1.8    | Energy hazards – d.c. mains supply   | Equipment is not intended for connection to d.c. mains.               | N/A |
|            | a) Capacitor connected to the d.c. mains supply ...:   | -   | N/A |
|            | b) Internal battery connected to the d.c. mains supply :   | -   | N/A |
| 2.1.1.9    | Audio amplifiers .....   | No audio outputs.   | N/A |
| 2.1.2      | Protection in service access areas   | Checked by inspection.  | P   |
| 2.1.3      | Protection in restricted access locations  | Equipment not intended for installation in RAL.                       | N/A |

|            |  |   |   |
|------------|--|---|---|
| <b>2.2</b> | <b>SELV circuits</b>                       |   | P |
| 2.2.1      | General requirements                       | 2.2.1 – 2.2.4; The EUT is supplied from a SELV circuit. The equipment contains only SELV circuits and there are no components that could rise voltage above SELV limits in fault condition. | P |
| 2.2.2      | Voltages under normal conditions (V) ..... | Within SELV limits.   | P |
| 2.2.3      | Voltages under fault conditions (V) .....  | Within SELV limits.   | P |

| <b>IEC 60950-1</b> |  |  |         |
|--------------------|--|--|---------|
| Clause             | Requirement + Test                                       | Result - Remark  | Verdict |
| 2.2.4              | Connection of SELV circuits to other circuits .....      | SELV circuits are only connected to other SELV circuits. | P       |
| <b>2.3</b>         | <b>TNV circuits</b>                                      |  | N/A     |
| 2.3.1              | Limits   | No TNV.  | N/A     |
|                    | Type of TNV circuits .....                               | -  | —       |
| 2.3.2              | Separation from other circuits and from accessible parts | -  | N/A     |
| 2.3.2.1            | General requirements                                     | -  | N/A     |
| 2.3.2.2            | Protection by basic insulation                           | -  | N/A     |
| 2.3.2.3            | Protection by earthing                                   | -  | N/A     |
| 2.3.2.4            | Protection by other constructions .....                  | -  | N/A     |
| 2.3.3              | Separation from hazardous voltages                       | -  | N/A     |
|                    | Insulation employed .....                                | -  | —       |
| 2.3.4              | Connection of TNV circuits to other circuits             | -  | N/A     |
|                    | Insulation employed .....                                | -  | —       |
| 2.3.5              | Test for operating voltages generated externally         | -  | N/A     |
| <b>2.4</b>         | <b>Limited current circuits</b>                          |  | N/A     |
| 2.4.1              | General requirements                                     | No limited current circuits.                             | N/A     |
| 2.4.2              | Limit values   | -  | N/A     |
|                    | Frequency (Hz) .....                                     | -  | —       |
|                    | Measured current (mA) .....                              | -  | —       |
|                    | Measured voltage (V) .....                               | -  | —       |
|                    | Measured circuit capacitance (nF or µF) .....            | -  | —       |
| 2.4.3              | Connection of limited current circuits to other circuits | -  | N/A     |
| <b>2.5</b>         | <b>Limited power sources</b>                             |  | N/A     |

| <b>IEC 60950-1</b> |  |   |         |
|--------------------|--|---|---------|
| Clause             | Requirement + Test   | Result - Remark   | Verdict |
| <b>2.6</b>         | <b>Provisions for earthing and bonding</b>   |   | N/A     |
| 2.6.1              | Protective earthing  | Class III equipment, not connected to protective earth. | N/A     |
| 2.6.2              | Functional earthing  | -   | N/A     |
|                    | Use of symbol for functional earthing .....  | -   | N/A     |
| 2.6.3              | Protective earthing and protective bonding conductors  | -   | N/A     |
| 2.6.3.1            | General  | -   | N/A     |
| 2.6.3.2            | Size of protective earthing conductors   | -   | N/A     |
|                    | Rated current (A), cross-sectional area (mm <sup>2</sup> ), AWG .....  | -   | —       |
| 2.6.3.3            | Size of protective bonding conductors  | -   | N/A     |
|                    | Rated current (A), cross-sectional area (mm <sup>2</sup> ), AWG .....  | -   | —       |
|                    | Protective current rating (A), cross-sectional area (mm <sup>2</sup> ), AWG .....  | -   | —       |
| 2.6.3.4            | Resistance of earthing conductors and their terminations; resistance (Ω), voltage drop (V), test current (A), duration (min) ..... | -   | N/A     |
| 2.6.3.5            | Colour of insulation.....  | -   | N/A     |
| 2.6.4              | Terminals  | -   | N/A     |
| 2.6.4.1            | General  | -   | N/A     |
| 2.6.4.2            | Protective earthing and bonding terminals  | -   | N/A     |
|                    | Rated current (A), type, nominal thread diameter (mm) .....  | -   | —       |
| 2.6.4.3            | Separation of the protective earthing conductor from protective bonding conductors   | -   | N/A     |
| 2.6.5              | Integrity of protective earthing   | -   | N/A     |
| 2.6.5.1            | Interconnection of equipment   | -   | N/A     |
| 2.6.5.2            | Components in protective earthing conductors and protective bonding conductors   | -   | N/A     |
| 2.6.5.3            | Disconnection of protective earth  | -   | N/A     |
| 2.6.5.4            | Parts that can be removed by an operator   | -   | N/A     |
| 2.6.5.5            | Parts removed during servicing   | -   | N/A     |
| 2.6.5.6            | Corrosion resistance   | -   | N/A     |
| 2.6.5.7            | Screws for protective bonding  | -   | N/A     |
| 2.6.5.8            | Reliance on telecommunication network or cable distribution system   | -   | N/A     |



| IEC 60950-1 |                    |                 |         |
|-------------|--------------------|-----------------|---------|
| Clause      | Requirement + Test | Result - Remark | Verdict |

|            |   |                      |     |
|------------|---|----------------------|-----|
| <b>2.7</b> | <b>Overcurrent and earth fault protection in primary circuits</b> |                      | N/A |
| 2.7.1      | Basic requirements  | Class III equipment. | N/A |
|            | Instructions when protection relies on building installation      | -                    | N/A |
| 2.7.2      | Faults not simulated in 5.3.7                                     | -                    | N/A |
| 2.7.3      | Short-circuit backup protection                                   | -                    | N/A |
| 2.7.4      | Number and location of protective devices .....                   | -                    | N/A |
| 2.7.5      | Protection by several devices                                     | -                    | N/A |
| 2.7.6      | Warning to service personnel.....                                 | -                    | N/A |

|            |   |                                |     |
|------------|---|--------------------------------|-----|
| <b>2.8</b> | <b>Safety interlocks</b>  |                                | N/A |
| 2.8.1      | General principles  | No safety interlocks required. | N/A |
| 2.8.2      | Protection requirements   | -                              | N/A |
| 2.8.3      | Inadvertent reactivation  | -                              | N/A |
| 2.8.4      | Fail-safe operation   | -                              | N/A |
|            | Protection against extreme hazard   | -                              | N/A |
| 2.8.5      | Moving parts  | -                              | N/A |
| 2.8.6      | Overriding  | -                              | N/A |
| 2.8.7      | Switches, relays and their related circuits                                 | -                              | N/A |
| 2.8.7.1    | Separation distances for contact gaps and their related circuits (mm) ..... | -                              | N/A |
| 2.8.7.2    | Overload test   | -                              | N/A |
| 2.8.7.3    | Endurance test  | -                              | N/A |
| 2.8.7.4    | Electric strength test  | -                              | N/A |
| 2.8.8      | Mechanical actuators  | -                              | N/A |

|            |   |   |     |
|------------|---|---|-----|
| <b>2.9</b> | <b>Electrical insulation</b>                  |   | P   |
| 2.9.1      | Properties of insulating materials            | Neither natural rubber, materials containing asbestos nor hygroscopic materials are used as insulation. No driving belts or couplings used. | P   |
| 2.9.2      | Humidity conditioning                         | No hygroscopic materials used.  | N/A |
|            | Relative humidity (%), temperature (°C) ..... | -   | —   |
| 2.9.3      | Grade of insulation                           | Insulation is considered to be functional.  | P   |
| 2.9.4      | Separation from hazardous voltages            | Class III equipment.  | N/A |
|            | Method(s) used .....                          | -   | —   |

| IEC 60950-1 |   |   |         |
|-------------|---|---|---------|
| Clause      | Requirement + Test  | Result - Remark   | Verdict |
| <b>2.10</b> | <b>Clearances, creepage distances and distances through insulation</b>          |   | P       |
| 2.10.1      | General   | 2.10.1 – 2.10.12; Class III equipment. All insulation is considered functional only, ref. 5.3.4 c). | P       |
| 2.10.1.1    | Frequency .....   | -   | N/A     |
| 2.10.1.2    | Pollution degrees .....   | -   | N/A     |
| 2.10.1.3    | Reduced values for functional insulation  | -   | N/A     |
| 2.10.1.4    | Intervening unconnected conductive parts  | -   | N/A     |
| 2.10.1.5    | Insulation with varying dimensions  | -   | N/A     |
| 2.10.1.6    | Special separation requirements   | -   | N/A     |
| 2.10.1.7    | Insulation in circuits generating starting pulses                               | -   | N/A     |
| 2.10.2      | Determination of working voltage  | -   | N/A     |
| 2.10.2.1    | General   | -   | N/A     |
| 2.10.2.2    | RMS working voltage   | -   | N/A     |
| 2.10.2.3    | Peak working voltage  | -   | N/A     |
| 2.10.3      | Clearances  | -   | N/A     |
| 2.10.3.1    | General   | -   | N/A     |
| 2.10.3.2    | Mains transient voltages  | -   | N/A     |
|             | a) AC mains supply .....  | -   | N/A     |
|             | b) Earthed d.c. mains supplies .....  | -   | N/A     |
|             | c) Unearthed d.c. mains supplies .....  | -   | N/A     |
|             | d) Battery operation .....  | -   | N/A     |
| 2.10.3.3    | Clearances in primary circuits  | -   | N/A     |
| 2.10.3.4    | Clearances in secondary circuits  | Only functional insulation in secondary circuits. Refer 5.3.4 c).                                   | P       |
| 2.10.3.5    | Clearances in circuits having starting pulses                                   | -   | N/A     |
| 2.10.3.6    | Transients from a.c. mains supply .....   | -   | N/A     |
| 2.10.3.7    | Transients from d.c. mains supply .....   | -   | N/A     |
| 2.10.3.8    | Transients from telecommunication networks and cable distribution systems ..... | -   | N/A     |
| 2.10.3.9    | Measurement of transient voltage levels   | -   | N/A     |
|             | a) Transients from a mains supply   | -   | N/A     |
|             | For an a.c. mains supply .....  | -   | N/A     |
|             | For a d.c. mains supply .....   | -   | N/A     |
|             | b) Transients from a telecommunication network :                                | -   | N/A     |
| 2.10.4      | Creepage distances  | -   | N/A     |
| 2.10.4.1    | General   | -   | N/A     |

| IEC 60950-1 |   |                 |         |
|-------------|---|-----------------|---------|
| Clause      | Requirement + Test  | Result - Remark | Verdict |
| 2.10.4.2    | Material group and comparative tracking index                                   | -               | N/A     |
|             | CTI tests .....   | -               | —       |
| 2.10.4.3    | Minimum creepage distances  | -               | N/A     |
| 2.10.5      | Solid insulation  | -               | N/A     |
| 2.10.5.1    | General   | -               | N/A     |
| 2.10.5.2    | Distances through insulation  | -               | N/A     |
| 2.10.5.3    | Insulating compound as solid insulation   | -               | N/A     |
| 2.10.5.4    | Semiconductor devices   | -               | N/A     |
| 2.10.5.5.   | Cemented joints   | -               | N/A     |
| 2.10.5.6    | Thin sheet material – General   | -               | N/A     |
| 2.10.5.7    | Separable thin sheet material   | -               | N/A     |
|             | Number of layers (pcs) .....  | -               | —       |
| 2.10.5.8    | Non-separable thin sheet material   | -               | N/A     |
| 2.10.5.9    | Thin sheet material – standard test procedure                                   | -               | N/A     |
|             | Electric strength test  | -               | —       |
| 2.10.5.10   | Thin sheet material – alternative test procedure                                | -               | N/A     |
|             | Electric strength test  | -               | —       |
| 2.10.5.11   | Insulation in wound components  | -               | N/A     |
| 2.10.5.12   | Wire in wound components  | -               | N/A     |
|             | Working voltage .....   | -               | N/A     |
|             | a) Basic insulation not under stress .....                                      | -               | N/A     |
|             | b) Basic, supplementary, reinforced insulation .....                            | -               | N/A     |
|             | c) Compliance with Annex U .....  | -               | N/A     |
|             | Two wires in contact inside wound component;<br>angle between 45° and 90° ..... | -               | N/A     |
| 2.10.5.13   | Wire with solvent-based enamel in wound components                              | -               | N/A     |
|             | Electric strength test  | -               | —       |
|             | Routine test  | -               | N/A     |
| 2.10.5.14   | Additional insulation in wound components                                       | -               | N/A     |
|             | Working voltage .....   | -               | N/A     |
|             | - Basic insulation not under stress .....                                       | -               | N/A     |
|             | - Supplementary, reinforced insulation .....                                    | -               | N/A     |
| 2.10.6      | Construction of printed boards  | -               | N/A     |
| 2.10.6.1    | Uncoated printed boards   | -               | N/A     |
| 2.10.6.2    | Coated printed boards   | -               | N/A     |
| 2.10.6.3    | Insulation between conductors on the same inner surface of a printed board      | -               | N/A     |

| IEC 60950-1 |  |                 |         |
|-------------|--|-----------------|---------|
| Clause      | Requirement + Test   | Result - Remark | Verdict |
| 2.10.6.4    | Insulation between conductors on different layers of a printed board | -               | N/A     |
|             | Distance through insulation  | -               | N/A     |
|             | Number of insulation layers (pcs).....:                              | -               | N/A     |
| 2.10.7      | Component external terminations                                      | -               | N/A     |
| 2.10.8      | Tests on coated printed boards and coated components                 | -               | N/A     |
| 2.10.8.1    | Sample preparation and preliminary inspection                        | -               | N/A     |
| 2.10.8.2    | Thermal conditioning   | -               | N/A     |
| 2.10.8.3    | Electric strength test   | -               | N/A     |
| 2.10.8.4    | Abrasion resistance test   | -               | N/A     |
| 2.10.9      | Thermal cycling  | -               | N/A     |
| 2.10.10     | Test for Pollution Degree 1 environment and insulating compound      | -               | N/A     |
| 2.10.11     | Tests for semiconductor devices and cemented joints                  | -               | N/A     |
| 2.10.12     | Enclosed and sealed parts  | -               | N/A     |

| IEC 60950-1 |  |  |          |
|-------------|--|--|----------|
| Clause      | Requirement + Test                             | Result - Remark  | Verdict  |
| <b>3</b>    | <b>WIRING, CONNECTIONS AND SUPPLY</b>          |  | <b>P</b> |
| <b>3.1</b>  | <b>General</b>                                 |  | <b>P</b> |
| 3.1.1       | Current rating and overcurrent protection      | Adequate cross sectional areas on internal wiring.   | P        |
| 3.1.2       | Protection against mechanical damage           | Wireways are smooth and free from edges. Wires are adequately fixed to prevent excessive strain on wire and terminals and avoiding damage to the insulation of the conductors. | P        |
| 3.1.3       | Securing of internal wiring                    | Internal wiring is secured against excessive strain, loosening of terminals and damage to the conductor insulation.  | P        |
| 3.1.4       | Insulation of conductors                       | Insulation on internal conductors is considered to be of adequate quality and suitable for the application and the working voltage involved.                                   | P        |
| 3.1.5       | Beads and ceramic insulators                   | No beads or similar ceramic insulators on conductors.  | N/A      |
| 3.1.6       | Screws for electrical contact pressure         | No screws used for electrical contact pressure.  | N/A      |
| 3.1.7       | Insulating materials in electrical connections | No contact pressure through insulating material.   | N/A      |
| 3.1.8       | Self-tapping and spaced thread screws          | None used for electrical connections.  | N/A      |
| 3.1.9       | Termination of conductors                      | Terminations cannot become displaced so that clearances and creepage distances can be reduced. Insulation is only functional.  | N/A      |
|             | 10 N pull test                                 | -  | N/A      |
| 3.1.10      | Sleeving on wiring                             | No wiring with sleeving.   | N/A      |

| IEC 60950-1 |                    |                 |         |
|-------------|--------------------|-----------------|---------|
| Clause      | Requirement + Test | Result - Remark | Verdict |

|            |   |   |     |
|------------|---|---|-----|
| <b>3.2</b> | <b>Connection to a mains supply</b>                                   |   | N/A |
| 3.2.1      | Means of connection   | Class III equipment. The EUT is connected to a SELV through an internal separately certified terminal block with reference J02. | N/A |
| 3.2.1.1    | Connection to an a.c. mains supply                                    | -   | N/A |
| 3.2.1.2    | Connection to a d.c. mains supply                                     | -   | N/A |
| 3.2.2      | Multiple supply connections   | -   | N/A |
| 3.2.3      | Permanently connected equipment                                       | -   | N/A |
|            | Number of conductors, diameter of cable and conduits (mm) .....       | -   | —   |
| 3.2.4      | Appliance inlets  | -   | N/A |
| 3.2.5      | Power supply cords  | -   | N/A |
| 3.2.5.1    | AC power supply cords   | -   | N/A |
|            | Type .....  | -   | —   |
|            | Rated current (A), cross-sectional area (mm <sup>2</sup> ), AWG ..... | -   | —   |
| 3.2.5.2    | DC power supply cords   | -   | N/A |
| 3.2.6      | Cord anchorages and strain relief                                     | -   | N/A |
|            | Mass of equipment (kg), pull (N) .....                                | -   | —   |
|            | Longitudinal displacement (mm) .....                                  | -   | —   |
| 3.2.7      | Protection against mechanical damage                                  | -   | N/A |
| 3.2.8      | Cord guards   | -   | N/A |
|            | Diameter or minor dimension D (mm); test mass (g) .....               | -   | —   |
|            | Radius of curvature of cord (mm) .....                                | -   | —   |
| 3.2.9      | Supply wiring space   | -   | N/A |

|            |   |   |     |
|------------|---|---|-----|
| <b>3.3</b> | <b>Wiring terminals for connection of external conductors</b>                     |   | N/A |
| 3.3.1      | Wiring terminals  | Class III equipment. The EUT is connected to a SELV through an internal separately certified terminal block with reference J02. | N/A |
| 3.3.2      | Connection of non-detachable power supply cords                                   | -   | N/A |
| 3.3.3      | Screw terminals   | -   | N/A |
| 3.3.4      | Conductor sizes to be connected   | -   | N/A |
|            | Rated current (A), cord/cable type, cross-sectional area (mm <sup>2</sup> ) ..... | -   | —   |

| <b>IEC 60950-1</b> |                    |                 |         |
|--------------------|--------------------|-----------------|---------|
| Clause             | Requirement + Test | Result - Remark | Verdict |

|       |   |   |     |
|-------|---|---|-----|
| 3.3.5 | Wiring terminal sizes                                       | - | N/A |
|       | Rated current (A), type, nominal thread diameter (mm) ..... | - | —   |
| 3.3.6 | Wiring terminal design                                      | - | N/A |
| 3.3.7 | Grouping of wiring terminals                                | - | N/A |
| 3.3.8 | Stranded wire   | - | N/A |

|            |   |                      |     |
|------------|---|----------------------|-----|
| <b>3.4</b> | <b>Disconnection from the mains supply</b>        |                      | N/A |
| 3.4.1      | General requirement                               | Class III equipment. | N/A |
| 3.4.2      | Disconnect devices                                | -                    | N/A |
| 3.4.3      | Permanently connected equipment                   | -                    | N/A |
| 3.4.4      | Parts which remain energized                      | -                    | N/A |
| 3.4.5      | Switches in flexible cords                        | -                    | N/A |
| 3.4.6      | Number of poles - single-phase and d.c. equipment | -                    | N/A |
| 3.4.7      | Number of poles - three-phase equipment           | -                    | N/A |
| 3.4.8      | Switches as disconnect devices                    | -                    | N/A |
| 3.4.9      | Plugs as disconnect devices                       | -                    | N/A |
| 3.4.10     | Interconnected equipment                          | -                    | N/A |
| 3.4.11     | Multiple power sources                            | -                    | N/A |

|            |  |  |     |
|------------|--|--|-----|
| <b>3.5</b> | <b>Interconnection of equipment</b>      |  | P   |
| 3.5.1      | General requirements                     | Refer below.   | P   |
| 3.5.2      | Types of interconnection circuits .....  | SELV circuits only.                                    | P   |
| 3.5.3      | ELV circuits as interconnection circuits | No ELV.  | N/A |
| 3.5.4      | Data ports for additional equipment      | No data ports supplying power to additional equipment. | N/A |

| IEC 60950-1 |                    |                 |         |
|-------------|--------------------|-----------------|---------|
| Clause      | Requirement + Test | Result - Remark | Verdict |

|            |                              |                            |            |
|------------|------------------------------|----------------------------|------------|
| <b>4</b>   | <b>PHYSICAL REQUIREMENTS</b> |                            | <b>P</b>   |
| <b>4.1</b> | <b>Stability</b>             |                            | <b>N/A</b> |
|            | Angle of 10°                 | Wall mounted equipment.    | <b>N/A</b> |
|            | Test force (N) ..... :       | Not a floor standing unit. | <b>N/A</b> |

|            |  |   |            |
|------------|--|---|------------|
| <b>4.2</b> | <b>Mechanical strength</b>                           |   | <b>P</b>   |
| 4.2.1      | General  | Complies with the requirement also after tests described have been applied. | <b>P</b>   |
|            | Rack-mounted equipment.                              | Not a rack-mounted equipment.   | <b>N/A</b> |
| 4.2.2      | Steady force test, 10 N                              | No hazardous voltages or parts.   | <b>N/A</b> |
| 4.2.3      | Steady force test, 30 N                              | No hazardous voltages or parts.   | <b>N/A</b> |
| 4.2.4      | Steady force test, 250 N                             | No hazardous voltages or parts.   | <b>N/A</b> |
| 4.2.5      | Impact test  | No hazardous voltages or parts.   | <b>N/A</b> |
|            | Fall test  | No hazardous voltages or parts.   | <b>N/A</b> |
|            | Swing test   | No hazardous voltages or parts.   | <b>N/A</b> |
| 4.2.6      | Drop test; height (mm) ..... :                       | Drop test not applicable.   | <b>N/A</b> |
| 4.2.7      | Stress relief test                                   | No hazardous voltages or parts.   | <b>N/A</b> |
| 4.2.8      | Cathode ray tubes                                    | No CRT in the equipment.  | <b>N/A</b> |
|            | Picture tube separately certified ..... :            | -   | <b>N/A</b> |
| 4.2.9      | High pressure lamps                                  | No high pressure lamp used.   | <b>N/A</b> |
| 4.2.10     | Wall or ceiling mounted equipment; force (N) ..... : | Test is performed at 50N.   | <b>P</b>   |



| <b>IEC 60950-1</b> |  |  |          |
|--------------------|--|--|----------|
| Clause             | Requirement + Test                                     | Result - Remark  | Verdict  |
| <b>4.3</b>         | <b>Design and construction</b>                         |  | <b>P</b> |
| 4.3.1              | Edges and corners                                      | All edges and corners are rounded and/or smoothed.   | P        |
| 4.3.2              | Handles and manual controls; force (N) .....           | No handles or manual controls.   | N/A      |
| 4.3.3              | Adjustable controls                                    | No adjustable controls.  | N/A      |
| 4.3.4              | Securing of parts                                      | No hazardous voltages inside.  | N/A      |
| 4.3.5              | Connection by plugs and sockets                        | SELV connectors do not comply with IEC 60320 or IEC 60083.<br>Connector(s) (are) is only accessible to service persons, adequate marking provided. | P        |
| 4.3.6              | Direct plug-in equipment                               | Class III equipment.   | N/A      |
|                    | Torque .....   | -  | —        |
|                    | Compliance with the relevant mains plug standard ..... | -  | N/A      |
| 4.3.7              | Heating elements in earthed equipment                  | No heating elements.   | N/A      |
| 4.3.8              | Batteries  | No batteries.  | N/A      |
|                    | - Overcharging of a rechargeable battery               | -  | N/A      |
|                    | - Unintentional charging of a non-rechargeable battery | -  | N/A      |
|                    | - Reverse charging of a rechargeable battery           | -  | N/A      |
|                    | - Excessive discharging rate for any battery           | -  | N/A      |
| 4.3.9              | Oil and grease   | Insulation is not exposed to oil, grease etc.  | N/A      |
| 4.3.10             | Dust, powders, liquids and gases                       | The equipment does not generate dust or use powders, liquids or gases.   | N/A      |
| 4.3.11             | Containers for liquids or gases                        | The equipment does not contain liquids or gases.   | N/A      |
| 4.3.12             | Flammable liquids .....                                | The equipment does not contain flammable liquids.  | N/A      |
|                    | Quantity of liquid (l) .....                           | -  | N/A      |
|                    | Flash point (°C) .....                                 | -  | N/A      |
| 4.3.13             | Radiation  | Refer below.   | P        |
| 4.3.13.1           | General  | Refer below.   | P        |
| 4.3.13.2           | Ionizing radiation                                     | The equipment does not generate ionizing radiation.  | N/A      |
|                    | Measured radiation (pA/kg) .....                       | -  | —        |
|                    | Measured high-voltage (kV) .....                       | -  | —        |
|                    | Measured focus voltage (kV) .....                      | -  | —        |

| IEC 60950-1 |   |   |         |
|-------------|---|---|---------|
| Clause      | Requirement + Test  | Result - Remark                               | Verdict |
|             | CRT markings .....  | -   | —       |
| 4.3.13.3    | Effect of ultraviolet (UV) radiation on materials                       | The equipment does not generate UV radiation. | N/A     |
|             | Part, property, retention after test, flammability classification ..... | -   | N/A     |
| 4.3.13.4    | Human exposure to ultraviolet (UV) radiation .....                      | The equipment does not generate UV radiation. | N/A     |
| 4.3.13.5    | Lasers (including laser diodes) and LEDs                                | Refer below.                                  | P       |
| 4.3.13.5.1  | Lasers (including laser diodes)   | No laser in the equipment.                    | N/A     |
|             | Laser class .....   | -   | —       |
| 4.3.13.5.2  | Light emitting diodes (LEDs)  | LEDs are diffused type.                       | P       |
| 4.3.13.6    | Other types .....   |   | N/A     |

|            |  |                  |     |
|------------|--|------------------|-----|
| <b>4.4</b> | <b>Protection against hazardous moving parts</b>   |                  | N/A |
| 4.4.1      | General  | No moving parts. | N/A |
| 4.4.2      | Protection in operator access areas .....          | -                | N/A |
|            | Household and home/office document/media shredders | -                | N/A |
| 4.4.3      | Protection in restricted access locations .....    | -                | N/A |
| 4.4.4      | Protection in service access areas                 | -                | N/A |
| 4.4.5      | Protection against moving fan blades               | -                | N/A |
| 4.4.5.1    | General  | -                | N/A |
|            | Not considered to cause pain or injury. a).....    | -                | N/A |
|            | Is considered to cause pain, not injury. b) .....  | -                | N/A |
|            | Considered to cause injury. c) .....               | -                | N/A |
| 4.4.5.2    | Protection for users                               | -                | N/A |
|            | Use of symbol or warning .....                     | -                | N/A |
| 4.4.5.3    | Protection for service persons                     | -                | N/A |
|            | Use of symbol or warning .....                     | -                | N/A |

| IEC 60950-1 |                    |                 |         |
|-------------|--------------------|-----------------|---------|
| Clause      | Requirement + Test | Result - Remark | Verdict |

|            |   |   |     |
|------------|---|---|-----|
| <b>4.5</b> | <b>Thermal requirements</b>               |   | P   |
| 4.5.1      | General                                   | Refer below.  | P   |
| 4.5.2      | Temperature tests                         | (see appended table 4.5)                            | P   |
|            | Normal load condition per Annex L ..... : | Tested in a system. See summary of testing.         | —   |
| 4.5.3      | Temperature limits for materials          | (see appended table 4.5)                            | P   |
| 4.5.4      | Touch temperature limits                  | (see appended table 4.5)                            | P   |
| 4.5.5      | Resistance to abnormal heat ..... :       | No thermoplastic parts carrying hazardous voltages. | N/A |

|            |   |   |     |
|------------|---|---|-----|
| <b>4.6</b> | <b>Openings in enclosures</b>                       |   | P   |
| 4.6.1      | Top and side openings                               | No top openings in the enclosure.<br>Openings rear side:  | P   |
|            | Dimensions (mm) ..... :                             | 5.0 x 8.0mm (10 holes)  | —   |
| 4.6.2      | Bottoms of fire enclosures                          | No openings.  | P   |
|            | Construction of the bottom, dimensions (mm) ..... : | -   | —   |
| 4.6.3      | Doors or covers in fire enclosures                  | Cover removable, installation manual applied. Instructions given in manual for mounting/installation, including opening of cover. | P   |
| 4.6.4      | Openings in transportable equipment                 | The unit is not regarded as transportable equipment.  | N/A |
| 4.6.4.1    | Constructional design measures                      | -   | N/A |
|            | Dimensions (mm) ..... :                             | -   | —   |
| 4.6.4.2    | Evaluation measures for larger openings             | -   | N/A |
| 4.6.4.3    | Use of metallized parts                             | -   | N/A |
| 4.6.5      | Adhesives for constructional purposes               | No adhesive used.   | N/A |
|            | Conditioning temperature (°C), time (weeks) ..... : | -   | —   |

| IEC 60950-1 |                    |                 |         |
|-------------|--------------------|-----------------|---------|
| Clause      | Requirement + Test | Result - Remark | Verdict |

|            |  |   |     |
|------------|--|---|-----|
| <b>4.7</b> | <b>Resistance to fire</b>  |   | P   |
| 4.7.1      | Reducing the risk of ignition and spread of flame                      | Method 1 is used.   | P   |
|            | Method 1, selection and application of components wiring and materials | (see appended table 4.7)  | P   |
|            | Method 2, application of all of simulated fault condition tests        | -   | N/A |
| 4.7.2      | Conditions for a fire enclosure  | Refer below.  | P   |
| 4.7.2.1    | Parts requiring a fire enclosure                                       | All parts.  | P   |
| 4.7.2.2    | Parts not requiring a fire enclosure                                   | -   | N/A |
| 4.7.3      | Materials  |   | P   |
| 4.7.3.1    | General  | Components and materials have adequate flammability classification. See appended table 1.5.1.                 | P   |
| 4.7.3.2    | Materials for fire enclosures  | The enclosure is of 5VB plastic material.   | P   |
| 4.7.3.3    | Materials for components and other parts outside fire enclosures       | Same as for 4.7.3.2.  | P   |
| 4.7.3.4    | Materials for components and other parts inside fire enclosures        | Other materials inside enclosure are minimum V-2 material or small components mounted on PCB of V-0 material. | P   |
| 4.7.3.5    | Materials for air filter assemblies                                    | No air filters used.  | N/A |
| 4.7.3.6    | Materials used in high-voltage components                              | No high-voltage components.   | N/A |

| IEC 60950-1 |                    |                 |         |
|-------------|--------------------|-----------------|---------|
| Clause      | Requirement + Test | Result - Remark | Verdict |

|            |   |   |     |
|------------|---|---|-----|
| <b>5</b>   | <b>ELECTRICAL REQUIREMENTS AND SIMULATED ABNORMAL CONDITIONS</b>  |   | P   |
| <b>5.1</b> | <b>Touch current and protective conductor current</b>   |   | N/A |
| 5.1.1      | General   | 5.1.1 – 5.1.8.2; Class III equipment supplied by SELV. No TNV circuits. | N/A |
| 5.1.2      | Configuration of equipment under test (EUT)   | -   | N/A |
| 5.1.2.1    | Single connection to an a.c. mains supply   | -   | N/A |
| 5.1.2.2    | Redundant multiple connections to an a.c. mains supply  | -   | N/A |
| 5.1.2.3    | Simultaneous multiple connections to an a.c. mains supply   | -   | N/A |
| 5.1.3      | Test circuit  | -   | N/A |
| 5.1.4      | Application of measuring instrument   | -   | N/A |
| 5.1.5      | Test procedure  | -   | N/A |
| 5.1.6      | Test measurements   | -   | N/A |
|            | Supply voltage (V) .....  | -   | —   |
|            | Measured touch current (mA) .....   | -   | —   |
|            | Max. allowed touch current (mA) .....   | -   | —   |
|            | Measured protective conductor current (mA) .....  | -   | —   |
|            | Max. allowed protective conductor current (mA) ..   | -   | —   |
| 5.1.7      | Equipment with touch current exceeding 3,5 mA   | -   | N/A |
| 5.1.7.1    | General .....   | -   | N/A |
| 5.1.7.2    | Simultaneous multiple connections to the supply   | -   | N/A |
| 5.1.8      | Touch currents to telecommunication networks and cable distribution systems and from telecommunication networks | -   | N/A |
| 5.1.8.1    | Limitation of the touch current to a telecommunication network or to a cable distribution system                | -   | N/A |
|            | Supply voltage (V) .....  | -   | —   |
|            | Measured touch current (mA) .....   | -   | —   |
|            | Max. allowed touch current (mA) .....   | -   | —   |
| 5.1.8.2    | Summation of touch currents from telecommunication networks   | -   | N/A |
|            | a) EUT with earthed telecommunication ports .....   | -   | N/A |
|            | b) EUT whose telecommunication ports have no reference to protective earth                                      | -   | N/A |

| <b>IEC 60950-1</b> |                           |                        |                |
|--------------------|---------------------------|------------------------|----------------|
| <b>Clause</b>      | <b>Requirement + Test</b> | <b>Result - Remark</b> | <b>Verdict</b> |

|            |                          |                      |     |
|------------|--------------------------|----------------------|-----|
| <b>5.2</b> | <b>Electric strength</b> |                      | N/A |
| 5.2.1      | General                  | Class III equipment. | N/A |
| 5.2.2      | Test procedure           | Class III equipment. | N/A |

|            |   |   |     |
|------------|---|---|-----|
| <b>5.3</b> | <b>Abnormal operating and fault conditions</b>                  |   | P   |
| 5.3.1      | Protection against overload and abnormal operation              | (see appended table 5.3)  | P   |
| 5.3.2      | Motors  | No motors in the equipment.   | N/A |
| 5.3.3      | Transformers  | No isolating transformers.  | N/A |
| 5.3.4      | Functional insulation .....                                     | Complies with c).<br>Components mounted on V-0 material PCB.                      | P   |
| 5.3.5      | Electromechanical components                                    | No electromechanical components in secondary circuits.                            | N/A |
| 5.3.6      | Audio amplifiers in ITE .....                                   | No audio outputs.   | N/A |
| 5.3.7      | Simulation of faults  | (see appended table 5.3)  | P   |
| 5.3.8      | Unattended equipment  | No thermostats, temperature limiters or thermal cut-outs.                         | N/A |
| 5.3.9      | Compliance criteria for abnormal operating and fault conditions | Refer below.  | P   |
| 5.3.9.1    | During the tests  | No fire or molten metal occurred and no deformation of enclosure during the tests | P   |
| 5.3.9.2    | After the tests   | -   | P   |

|          |   |  |     |
|----------|---|--|-----|
| <b>6</b> | <b>CONNECTION TO TELECOMMUNICATION NETWORKS</b> |  | N/A |
|----------|---|--|-----|

|            |  |  |     |
|------------|--|--|-----|
| <b>6.1</b> | <b>Protection of telecommunication network service persons, and users of other equipment connected to the network, from hazards in the equipment</b> |  | N/A |
|------------|--|--|-----|

|            |  |  |     |
|------------|--|--|-----|
| <b>6.2</b> | <b>Protection of equipment users from overvoltages on telecommunication networks</b> |  | N/A |
|------------|--|--|-----|

|            |   |  |     |
|------------|---|--|-----|
| <b>6.3</b> | <b>Protection of the telecommunication wiring system from overheating</b> |  | N/A |
|------------|---|--|-----|

| <b>IEC 60950-1</b> |   |  |         |
|--------------------|---|--|---------|
| Clause             | Requirement + Test  | Result - Remark  | Verdict |
| <b>7</b>           | <b>CONNECTION TO CABLE DISTRIBUTION SYSTEMS</b>   |  | P       |
| <b>7.1</b>         | <b>General</b>  | -  | P       |
| 7.2                | Protection of cable distribution system service persons, and users of other equipment connected to the system, from hazardous voltages in the equipment | Circuits in the equipment intended to be directly connected to a cable distribution system complies with requirements for a TNV-1 circuit.                                   | P       |
| 7.3                | Protection of equipment users from overvoltages on the cable distribution system  | -  | P       |
| 7.4                | Insulation between primary circuits and cable distribution systems  | The EUT may be connected to an outdoor antenna.  | P       |
| 7.4.1              | General   | Complies, see 7.4.2.   | P       |
| 7.4.2              | Voltage surge test  | Fifty discharges are applied from the impulse test generator at a rate of 12 discharges per minute, with Uc equal to 10kV. Electric strength test performed after this test. | P       |
| 7.4.3              | Impulse test  | -  | N/A     |

| IEC 60950-1 |                    |                 |         |
|-------------|--------------------|-----------------|---------|
| Clause      | Requirement + Test | Result - Remark | Verdict |

|            |   |   |     |
|------------|---|---|-----|
| <b>A</b>   | <b>ANNEX A, TESTS FOR RESISTANCE TO HEAT AND FIRE</b>   |   | N/A |
| <b>A.1</b> | <b>Flammability test for fire enclosures of movable equipment having a total mass exceeding 18 kg, and of stationary equipment (see 4.7.3.2)</b>  | - | N/A |
| A.1.1      | Samples .....   | - | —   |
|            | Wall thickness (mm).....  | - | —   |
| A.1.2      | Conditioning of samples; temperature (°C) .....   | - | N/A |
| A.1.3      | Mounting of samples .....   | - | N/A |
| A.1.4      | Test flame (see IEC 60695-11-3)   | - | N/A |
|            | Flame A, B, C or D .....  | - | —   |
| A.1.5      | Test procedure  | - | N/A |
| A.1.6      | Compliance criteria   | - | N/A |
|            | Sample 1 burning time (s).....  | - | —   |
|            | Sample 2 burning time (s).....  | - | —   |
|            | Sample 3 burning time (s).....  | - | —   |
| <b>A.2</b> | <b>Flammability test for fire enclosures of movable equipment having a total mass not exceeding 18 kg, and for material and components located inside fire enclosures (see 4.7.3.2 and 4.7.3.4)</b> | - | N/A |
| A.2.1      | Samples, material .....   | - | —   |
|            | Wall thickness (mm).....  | - | —   |
| A.2.2      | Conditioning of samples; temperature (°C) .....   | - | N/A |
| A.2.3      | Mounting of samples .....   | - | N/A |
| A.2.4      | Test flame (see IEC 60695-11-4)   | - | N/A |
|            | Flame A, B or C .....   | - | —   |
| A.2.5      | Test procedure  | - | N/A |
| A.2.6      | Compliance criteria   | - | N/A |
|            | Sample 1 burning time (s).....  | - | —   |
|            | Sample 2 burning time (s).....  | - | —   |
|            | Sample 3 burning time (s).....  | - | —   |
| A.2.7      | Alternative test acc. to IEC 60695-11-5, cl. 5 and 9  | - | N/A |
|            | Sample 1 burning time (s).....  | - | —   |
|            | Sample 2 burning time (s).....  | - | —   |
|            | Sample 3 burning time (s).....  | - | —   |



| IEC 60950-1 |                    |                 |         |
|-------------|--------------------|-----------------|---------|
| Clause      | Requirement + Test | Result - Remark | Verdict |

|            |   |   |     |
|------------|---|---|-----|
| <b>A.3</b> | <b>Hot flaming oil test (see 4.6.2)</b> | - | N/A |
| A.3.1      | Mounting of samples                     | - | N/A |
| A.3.2      | Test procedure                          | - | N/A |
| A.3.3      | Compliance criterion                    | - | N/A |

|             |   |   |     |
|-------------|---|---|-----|
| <b>B</b>    | <b>ANNEX B, MOTOR TESTS UNDER ABNORMAL CONDITIONS (see 4.7.2.2 and 5.3.2)</b> |   | N/A |
| <b>B.1</b>  | <b>General requirements</b>   | - | N/A |
|             | Position .....  | - | —   |
|             | Manufacturer .....  | - | —   |
|             | Type .....  | - | —   |
|             | Rated values .....  | - | —   |
| <b>B.2</b>  | <b>Test conditions</b>  | - | N/A |
| <b>B.3</b>  | <b>Maximum temperatures</b>   | - | N/A |
| <b>B.4</b>  | <b>Running overload test</b>  | - | N/A |
| <b>B.5</b>  | <b>Locked-rotor overload test</b>   | - | N/A |
|             | Test duration (days) .....  | - | —   |
|             | Electric strength test: test voltage (V) .....                                | - | —   |
| <b>B.6</b>  | <b>Running overload test for d.c. motors in secondary circuits</b>            | - | N/A |
| B.6.1       | General   | - | N/A |
| B.6.2       | Test procedure  | - | N/A |
| B.6.3       | Alternative test procedure  | - | N/A |
| B.6.4       | Electric strength test; test voltage (V) .....                                | - | N/A |
| <b>B.7</b>  | <b>Locked-rotor overload test for d.c. motors in secondary circuits</b>       | - | N/A |
| B.7.1       | General   | - | N/A |
| B.7.2       | Test procedure  | - | N/A |
| B.7.3       | Alternative test procedure  | - | N/A |
| B.7.4       | Electric strength test; test voltage (V) .....                                | - | N/A |
| <b>B.8</b>  | <b>Test for motors with capacitors</b>  | - | N/A |
| <b>B.9</b>  | <b>Test for three-phase motors</b>  | - | N/A |
| <b>B.10</b> | <b>Test for series motors</b>   | - | N/A |
|             | Operating voltage (V) .....   | - | —   |

| IEC 60950-1 |  |                 |         |
|-------------|--|-----------------|---------|
| Clause      | Requirement + Test   | Result - Remark | Verdict |
| <b>C</b>    | <b>ANNEX C, TRANSFORMERS (see 1.5.4 and 5.3.3)</b>   |                 | N/A     |
|             | Position .....   | -               | —       |
|             | Manufacturer .....   | -               | —       |
|             | Type .....   | -               | —       |
|             | Rated values .....   | -               | —       |
|             | Method of protection .....   | -               | —       |
| <b>C.1</b>  | <b>Overload test</b>   | -               | N/A     |
| <b>C.2</b>  | <b>Insulation</b>  | -               | N/A     |
|             | Protection from displacement of windings .....   | -               | N/A     |
| <b>D</b>    | <b>ANNEX D, MEASURING INSTRUMENTS FOR TOUCH-CURRENT TESTS (see 5.1.4)</b>                                      |                 | N/A     |
| <b>E</b>    | <b>ANNEX E, TEMPERATURE RISE OF A WINDING (see 1.4.13)</b>   |                 | N/A     |
| <b>F</b>    | <b>ANNEX F, MEASUREMENT OF CLEARANCES AND CREEPAGE DISTANCES (see 2.10 and Annex G)</b>                        |                 | N/A     |
| <b>G</b>    | <b>ANNEX G, ALTERNATIVE METHOD FOR DETERMINING MINIMUM CLEARANCES</b>  |                 | N/A     |
| <b>H</b>    | <b>ANNEX H, IONIZING RADIATION (see 4.3.13)</b>  |                 | N/A     |
| <b>J</b>    | <b>ANNEX J, TABLE OF ELECTROCHEMICAL POTENTIALS (see 2.6.5.6)</b>  |                 | N/A     |
| <b>K</b>    | <b>ANNEX K, THERMAL CONTROLS (see 1.5.3 and 5.3.8)</b>   |                 | N/A     |
| <b>L</b>    | <b>ANNEX L, NORMAL LOAD CONDITIONS FOR SOME TYPES OF ELECTRICAL BUSINESS EQUIPMENT (see 1.2.2.1 and 4.5.2)</b> |                 | P       |
| L.1         | Typewriters  | -               | N/A     |
| L.2         | Adding machines and cash registers   | -               | N/A     |
| L.3         | Erasers  | -               | N/A     |
| L.4         | Pencil sharpeners  | -               | N/A     |
| L.5         | Duplicators and copy machines  | -               | N/A     |
| L.6         | Motor-operated files   | -               | N/A     |
| L.7         | Other business equipment   | Transmitter     | P       |

| IEC 60950-1 |   |                 |         |
|-------------|---|-----------------|---------|
| Clause      | Requirement + Test  | Result - Remark | Verdict |
| M           | ANNEX M, CRITERIA FOR TELEPHONE RINGING SIGNALS (see 2.3.1)   |                 | N/A     |
| N           | ANNEX N, IMPULSE TEST GENERATORS (see 1.5.7.2, 1.5.7.3, 2.10.3.9, 6.2.2.1, 7.3.2, 7.4.3 and Clause G.5) |                 | P       |
| P           | ANNEX P, NORMATIVE REFERENCES   |                 | —       |
| Q           | ANNEX Q, Voltage dependent resistors (VDRs) (see 1.5.9.1)   |                 | N/A     |
| R           | ANNEX R, EXAMPLES OF REQUIREMENTS FOR QUALITY CONTROL PROGRAMMES  |                 | N/A     |
| S           | ANNEX S, PROCEDURE FOR IMPULSE TESTING (see 6.2.2.3)  |                 | N/A     |
| T           | ANNEX T, GUIDANCE ON PROTECTION AGAINST INGRESS OF WATER (see 1.1.2)                                    |                 | N/A     |
| U           | ANNEX U, INSULATED WINDING WIRES FOR USE WITHOUT INTERLEAVED INSULATION (see 2.10.5.4)                  |                 | N/A     |
| V           | ANNEX V, AC POWER DISTRIBUTION SYSTEMS (see 1.6.1)  |                 | N/A     |
| W           | ANNEX W, SUMMATION OF TOUCH CURRENTS  |                 | N/A     |
| X           | ANNEX X, MAXIMUM HEATING EFFECT IN TRANSFORMER TESTS (see clause C.1)                                   |                 | N/A     |
| Y           | ANNEX Y, ULTRAVIOLET LIGHT CONDITIONING TEST (see 4.3.13.3)   |                 | N/A     |
| Z           | ANNEX Z, OVERVOLTAGE CATEGORIES (see 2.10.3.2 and Clause G.2)   |                 | N/A     |

| <b>IEC 60950-1</b> |  |                        |                |
|--------------------|--|------------------------|----------------|
| <b>Clause</b>      | <b>Requirement + Test</b>  | <b>Result - Remark</b> | <b>Verdict</b> |
| <b>AA</b>          | <b>ANNEX AA, MANDREL TEST (see 2.10.5.8)</b>                                   |                        | <b>N/A</b>     |
| <b>BB</b>          | <b>ANNEX BB, CHANGES IN THE SECOND EDITION</b>                                 |                        | —              |
| <b>CC</b>          | <b>ANNEX CC, Evaluation of integrated circuit (IC) current limiters</b>        |                        | <b>N/A</b>     |
| <b>DD</b>          | <b>ANNEX DD, Requirements for the mounting means of rack-mounted equipment</b> |                        | <b>N/A</b>     |
| <b>EE</b>          | <b>ANNEX EE, Household and home/office document/media shredders</b>            |                        | <b>N/A</b>     |

| IEC 60950-1 |                    |                 |         |
|-------------|--------------------|-----------------|---------|
| Clause      | Requirement + Test | Result - Remark | Verdict |

| 1.5.1   | TABLE: List of critical components |              |  |                              |  | P |
|---|------------------------------------|--------------|--|------------------------------|--|---|
| Object/part No.   | Manufacturer/<br>trademark         | Type/model   | Technical data   | Standard<br>(Edition / year) | Mark(s) of<br>conformity <sup>1)</sup> |   |
| (010730) PCB-material   | Various                            | FR4          | V-0  | UL 94                        | UL (E73072)                            |   |
| (M20238E)<br>(M280440)<br>Enclosure   | LG Chemical Ltd                    | GN-5001RF(T) | 5VB, ABS/PC<br>(min 1.5mm),<br>80°C                        | UL 94                        | UL (E67171)                            |   |
| (180456)<br>(Screw<br>Connector)  | Ria Connect Inc                    | Type 007     | 300V, 15A, 22-<br>12AWG, 125°C<br>Housing material:<br>V-0 | UL 1059                      | UL (E121004)                           |   |
| (180448) J102<br>(Plug)   | Ria Connect Inc                    | Type 017     | 300V, 15A,<br>125°C<br>Housing material:<br>V-0            | UL 1059                      | UL (E121004)                           |   |
| <b>Supplementary information:</b>   |                                    |              |  |                              |  |   |
| 1) Provided evidence ensures the agreed level of compliance. See OD-CB2039. |                                    |              |  |                              |  |   |
| The part no in parentheses are internal reference part no for Ascom.        |                                    |              |  |                              |  |   |

| IEC 60950-1 |                    |                 |         |
|-------------|--------------------|-----------------|---------|
| Clause      | Requirement + Test | Result - Remark | Verdict |

|   |                                       |  |     |
|---|---------------------------------------|--|-----|
| <b>1.5.1</b>                                | <b>TABLE: Opto Electronic Devices</b> |  | N/A |
| Manufacturer.....:                          |                                       |  |     |
| Type.....:                                  |                                       |  |     |
| Separately tested.....:                     |                                       |  |     |
| Bridging insulation .....                   |                                       |  |     |
| External creepage distance .....            |                                       |  |     |
| Internal creepage distance .....            |                                       |  |     |
| Distance through insulation .....           |                                       |  |     |
| Tested under the following conditions ..... |                                       |  |     |
| Input.....:                                 |                                       |  |     |
| Output .....                                |                                       |  |     |
| supplementary information                   |                                       |  |     |
|   |                                       |  |     |

| <b>1.6.2</b>                       | <b>TABLE: Electrical data (in normal conditions)</b> |                         |       |        |                        | P                |
|------------------------------------|--|-------------------------|-------|--------|------------------------|------------------|
| U (V)                              | I (mA)   | I <sub>rated</sub> (mA) | P (W) | Fuse # | I <sub>fuse</sub> (mA) | Condition/status |
| 11.25                              | 2505   | -                       | 28.2  | -      | -                      | Normal load      |
| 12.5                               | 2450   | 2500                    | 30.6  | -      | -                      | Normal load      |
| 13.75                              | 2445   | -                       | 33.6  | -      | -                      | Normal load      |
| Supplementary information:         |  |                         |       |        |                        |                  |
| * Max current rating model T938BC2 |  |                         |       |        |                        |                  |

|                      |                                  |     |
|----------------------|----------------------------------|-----|
| <b>2.1.1.5 c) 1)</b> | <b>TABLE: max. V, A, VA test</b> | N/A |
|----------------------|----------------------------------|-----|

|                      |                             |     |
|----------------------|-----------------------------|-----|
| <b>2.1.1.5 c) 2)</b> | <b>TABLE: stored energy</b> | N/A |
|----------------------|-----------------------------|-----|

|            |  |     |
|------------|--|-----|
| <b>2.2</b> | <b>TABLE: evaluation of voltage limiting components in SELV circuits</b> | N/A |
|------------|--|-----|

|            |                                     |     |
|------------|-------------------------------------|-----|
| <b>2.5</b> | <b>TABLE: Limited power sources</b> | N/A |
|------------|-------------------------------------|-----|

|               |   |     |
|---------------|---|-----|
| <b>2.10.2</b> | <b>Table: working voltage measurement</b> | N/A |
|---------------|---|-----|

| IEC 60950-1   |   |               |                         |                        |               |               |                 |                   |               |
|---|---|---------------|-------------------------|------------------------|---------------|---------------|-----------------|-------------------|---------------|
| Clause  | Requirement + Test                                  |               |                         |                        |               |               | Result - Remark |                   | Verdict       |
| 2.10.3 and 2.10.4   | TABLE: Clearance and creepage distance measurements |               |                         |                        |               |               |                 |                   | N/A           |
| 2.10.5  | TABLE: Distance through insulation measurements     |               |                         |                        |               |               |                 |                   | N/A           |
| 4.3.8   | TABLE: Batteries                                    |               |                         |                        |               |               |                 |                   | N/A           |
| The tests of 4.3.8 are applicable only when appropriate battery data is not available |   |               |                         |                        |               | -             |                 | N/A               |               |
| Is it possible to install the battery in a reverse polarity position?                 |   |               |                         |                        |               | -             |                 | N/A               |               |
|   | Non-rechargeable batteries                          |               |                         | Rechargeable batteries |               |               |                 |                   |               |
|   | Discharging   |               | Un-intentional charging | Charging               |               | Discharging   |                 | Reversed charging |               |
|   | Meas. current                                       | Manuf. Specs. |                         | Meas. current          | Manuf. Specs. | Meas. current | Manuf. Specs.   | Meas. current     | Manuf. Specs. |
| Max. current during normal condition  |   |               |                         |                        |               |               |                 |                   |               |
| Max. current during fault condition   |   |               |                         |                        |               |               |                 |                   |               |
| Test results:   |   |               |                         |                        |               |               |                 | Verdict           |               |
| - Chemical leaks  |   |               |                         |                        |               | -             |                 | N/A               |               |
| - Explosion of the battery  |   |               |                         |                        |               | -             |                 | N/A               |               |
| - Emission of flame or expulsion of molten metal                                      |   |               |                         |                        |               | -             |                 | N/A               |               |
| - Electric strength tests of equipment after completion of tests                      |   |               |                         |                        |               | -             |                 | N/A               |               |
| Supplementary information:  |   |               |                         |                        |               |               |                 |                   |               |

| IEC 60950-1 |                    |                 |         |
|-------------|--------------------|-----------------|---------|
| Clause      | Requirement + Test | Result - Remark | Verdict |

|   |                         |  |     |
|---|-------------------------|--|-----|
| <b>4.3.8</b>  | <b>TABLE: Batteries</b> |  | N/A |
| Battery category.....:<br>Manufacturer.....:<br>Type / model.....:<br>Voltage.....:<br>Capacity.....:<br>Tested and Certified by (incl. Ref. No.) .....:<br>Circuit protection diagram:<br><br> |                         |  |     |

| MARKINGS AND INSTRUCTIONS (1.7.13)  |  |
|-------------------------------------|--|
| Location of replaceable battery     |  |
| Language(s) .....                   |  |
| Close to the battery .....          |  |
| In the servicing instructions ..... |  |
| In the operating instructions ..... |  |

|   |   |        |       |  |  |  |                               |
|---|---|--------|-------|--|--|--|-------------------------------|
| <b>4.5</b>  | <b>TABLE: Thermal requirements</b>              |        |       |  |  |  | P                             |
|   | Supply voltage (V) .....                        | 12.5   | 12.5  |  |  |  | —                             |
|   | Ambient T <sub>max</sub> (°C) .....             | 26.2 * | 55 ** |  |  |  | —                             |
|   | Maximum measured temperature T of part/at.....: | T (°C) |       |  |  |  | Allowed T <sub>max</sub> (°C) |
|   | T100  | 29.6   | 58.4  |  |  |  | -                             |
|   | Enclosure                                       | 27.0   | 55.8  |  |  |  | 80 ***                        |
| Supplementary information:  |   |        |       |  |  |  |                               |
| * Temperatures measured at ambient temperature                      |   |        |       |  |  |  |                               |
| ** Temperatures corrected to 55°C (Recommended maximum temperature) |   |        |       |  |  |  |                               |
| *** Material rating   |   |        |       |  |  |  |                               |

|              |   |  |     |
|--------------|---|--|-----|
| <b>4.5.5</b> | <b>TABLE: Ball pressure test of thermoplastic parts</b> |  | N/A |
|--------------|---|--|-----|

|                            |                                  |                          |                  |                |                    |             |
|----------------------------|----------------------------------|--------------------------|------------------|----------------|--------------------|-------------|
| <b>4.7</b>                 | <b>TABLE: Resistance to fire</b> |                          |                  |                |                    | P           |
|                            | Part                             | Manufacturer of material | Type of material | Thickness (mm) | Flammability class | Evidence    |
|                            | Enclosure                        | LG Chemical Ltd          | ABS/PC           | Min. 1.5       | 5VB                | UL (E67171) |
| Supplementary information: |                                  |                          |                  |                |                    |             |

|            |   |  |     |
|------------|---|--|-----|
| <b>5.1</b> | <b>TABLE: touch current measurement</b> |  | N/A |
|------------|---|--|-----|



| IEC 60950-1 |                    |                 |         |
|-------------|--------------------|-----------------|---------|
| Clause      | Requirement + Test | Result - Remark | Verdict |

|            |  |  |     |
|------------|--|--|-----|
| <b>5.2</b> | <b>TABLE: Electric strength tests, impulse tests and voltage surge tests</b> |  | N/A |
|------------|--|--|-----|

|            |                                     |  |   |
|------------|-------------------------------------|--|---|
| <b>5.3</b> | <b>TABLE: Fault condition tests</b> |  | P |
|------------|-------------------------------------|--|---|

|  |                                |    |   |
|--|--------------------------------|----|---|
|  | Ambient temperature (°C) ..... | 25 | — |
|--|--------------------------------|----|---|

|  |   |                         |   |
|--|---|-------------------------|---|
|  | Power source for EUT: Manufacturer, model/type, output rating ..... | Chroma 6560 (150A, 80V) | — |
|--|---|-------------------------|---|

| Component No.       | Fault             | Supply voltage (Vdc) | Test time | Fuse # | Fuse current (mA) | Observation  |
|---------------------|-------------------|----------------------|-----------|--------|-------------------|--|
| C206 (952SM/FL PCB) | s-c               | 13.75                | 30 min    | -      | 0.6               | No change. R104/C101 heating up. No hazard.  |
| C127                | s-c               | 13.75                | 10 min    | -      | 2.2-0.6           | Unit shuts down. L103 heating up. No excessive temperatures.                                       |
| C113                | s-c               | 13.75                | 10 min    | -      | 2.6-0.5           | Unit shuts down. VR100 damaged. No hazard.   |
| C112                | s-c               | 13.75                | 10 min    | -      | 20-0.5            | D100 smoked. No hazard.  |
| C110                | s-c               | 13.75                | 2 hrs     | -      | 20                | Unit shuts down. No excessive temperatures obtained, terminal J02 slightly higher temp. No hazard. |
| Input +/-           | Reversed Polarity | 13.75                | 2 hrs     | -      | 20                | Unit shuts down. No excessive temperatures obtained, terminal J02 slightly higher temp. No hazard. |

Supplementary information:  
s-c = Short circuit.

Power source limited to 20A, power source limitations specified in installation manual.

|            |                            |  |     |
|------------|----------------------------|--|-----|
| <b>C.2</b> | <b>TABLE: transformers</b> |  | N/A |
|------------|----------------------------|--|-----|